

flex () vit

flex

the complete range of abrasive products for **MERCHANDISING PRODUCT CATALOGUE**

CONTENTS

INTRODUCTION

The Flexovit Merchandising Program	4
The Flexovit Brand History	5
A Corporate Perspective	5
How To Use This Catalogue	6
How To Order	6
Safety, Health, and Environment	7
Understanding the Flexovit Product Range	8
Pictograms	11
Merchandising Options	12

4

CUTTING-OFF AND GRINDING WHEELS

Useful Information	14
Cutting-Off Wheels	16
Grinding Wheels	20

13

BONDED ABRASIVES 21

- Useful Information Sharpening Stones
- Mounted Points
- Vitrified Bench Wheels

DIAMOND BLADES 53

Useful Information 54 5 – General Purpose 56

57

58

22

24

25

26

- Building Materials General Purpose
- Concrete and Reinforced Concrete
- Ceramic and Stone Tiles
- Roof Tiles, Granite and Hard Materials 59

Useful Information 28 Hand Sanding Sheets 30

COATED ABRASIVES 27

Hand Sanding Sheets	30
Sanding Rolls	35
Orbital Sheets	37
Sanding Discs	40
Multi Sanding Sheets	44
Sanding Belts	46
Sanding Block Kits & Sponges	50

ACCESSORIES 61

- Useful Information 62
- Steel Wire Wheels and Brushes 64
- Buffing & Polishing Products 66
 - Fibreflex Discs 67
- Backing Pads & Adaptor Shafts 68

NOTES AND INDEX 83

Notes 84 Index 86

TECHNICAL INFORMATION 69

71
73
77
79





INTRODUCTION

THE FLEXOVIT MERCHANDISING PROGRAM

Introducing the new Flexovit range of products for all retail and merchandising environments.

This completely new, exciting and professional product range consists of a comprehensive selection of coated abrasives, cutting-off and grinding wheels, diamond blades, bonded abrasives and accessories – supported by a very thorough and dynamic marketing program.

The Flexovit merchandising program has been created with the objective to improve your abrasive category revenue – 'helping you to sell more abrasives'.

The starting point is to provide a dynamic merchandising environment, focusing consumer attention and stimulating action. We can help to achieve through:

- Impact at point of purchase
- Clear product hierarchy encouraging 'trade-up'
- Ease of product selection
- Simple, uncluttered, attractive and informative design


We have also devised a simple, effective merchandising system based upon product use and value to the customer:

- Easy to display merchandising product packs
 - Smaller Pre-pack quantities
 - Larger Bulk pack quantities
 - Shelf Ready Packaging (bulk packs in self display boxes)
 - High Impact, informative and easy to use POP graphic panels

Flexovit already has an exceptional heritage. In industrial applications it provides a very complete collection of high performance and high value abrasives, commanding an excellent market image which spans the globe.

Dedicated to sanding, cutting, grinding and polishing, this Flexovit product range has been developed as a direct result of listening, understanding and responding to both market and customer requirements.

With this very complete multi-tiered product line which offers affordable, professional quality supported by a dynamic marketing program, we will help to better educate our users, to use proven industrial and new innovative abrasive products to improve their quality of finish, ease of use and speed of task – **helping you to improve your abrasives category revenue.**



THE FLEXOVIT BRAND HISTORY

Founded in the Netherlands, Flexovit began manufacturing cutting-off and grinding wheels in 1958. By 1960, Flexovit had carved out its ambition to become a global player and began exporting products across Europe. This international development continued throughout the 1960's and 70's fuelled by the introduction of automated production presses ensuring continued manufacture of high performance quality wheels. With an excellent brand reputation Flexovit began adding to its product portfolio with coated abrasives, bonded abrasives and construction products.



A CORPORATE PERSPECTIVE

Flexovit is a vital ingredient in an effective portfolio of brands from Saint-Gobain Abrasives. The mission is to deliver a portfolio of highly recognized brands with unique value, fulfilling the complete spectrum of customer needs.

Saint-Gobain Abrasives takes time to understand and fulfil its evolving customer needs and this is reflected in its worldwide market leader status. With a strong presence in every continent the Abrasives division serves its customers through structured units in 26 countries and employs nearly 16,000 people. It is the only international manufacturer to produce each of the three major types of abrasives; bonded abrasives (resinoid and vitrified), coated abrasives and diamond products. This is supported by exceptional technology, complete and innovative product lines, irrefutable reputation for quality and safety, and experienced, committed, passionate people.

Abrasives forms a key part of the High Performance Materials Division of Saint-Gobain, which is one of the 3 key areas of activity in which Saint-Gobain operate. The other 2 are Glass and Housing Products.

GLASS:				
Flat Glass	3rd worldwide			
Insulation	World leader			
Reinforcements	World leader			
Containers	2nd worldwide			
HOUSING PRODUCTS:				
Pipe	World leader for ductile iron pipes, fittings and municipal castings			
Building Materials	2nd worldwide			
Building Materials Distribution	No. 1 in Europe			
HIGH PERFORMANCE MATERIALS:				
Ceramics & Plastics	World leader for thermal & mechanical applications and high performance			
Abrasives	World leader			

Saint-Gobain is a world leader in each of these 3 areas and this commitment is reinforced through an annual global R&D investment of over 700 million. In 2005, Saint-Gobain employed over 182,000 people in more than 1,000 consolidated companies operating in 46 countries worldwide, with an annual turnover of more than €33 billion.



HOW TO USE THIS CATALOGUE

The catalogue is divided into colour coded sections by product type – cutting-off and grinding wheels, bonded abrasives, coated abrasives, diamond blades and accessories.

At the beginning of each section you will find useful information, including; Selecting the Right Product, Material Application Guide, Understanding the Product, and Differentiation within the Range. This is followed by informative and easy to use product charts. The charts include all of the information needed to make your selection.



HOW TO ORDER

Please contact your local Customer Service Centre, details can be found on the back page of the catalogue. For countries that are not listed please send your request to our European Headquarters.

When placing an order it helps to have the following information available:

Your name Your account number Your order or reference number Product article number/s Required quantity Any special instructions

If you require additional product or technical information then please do not hesitate to contact your local Customer Service or Sales Representative.

Prices

For prices and terms of sale please refer to the price list.

OUR RESPONSIBILITY – SAFETY, HEALTH, AND ENVIRONMENT

Activities

Our responsibility to customers, particularly in the area of safety and comfort, is taken very seriously. Products are designed and produced to the most stringent quality standards to guarantee optimum personal safety and user comfort. **Saint-Gobain Abrasives is an ac-**tive member of both FEPA and oSa.

Flexovit Merchandising products comply with all expectations of European health, safety and environmental standards.

FEPA, the Federation of European Producers of Abrasives, is dedicated to the promotion of safety in the use of abrasives and is actively involved in the preparation and implementation of the European (EN) and International Standards (ISO) for Abrasives and Grinding Machines.

oSa, the Organisation for Safety of Abrasives pursues in close collaboration with FEPA the objectives of supporting both the currently attained safety standards for abrasive products and their further developments.

The internal testing and certification is based on the following standards:

- Safety requirements for bonded abrasive products (EN 12413: 1999)
- Safety requirements for superabrasive products (EN 13236: 2001)
- Safety requirements for coated abrasives (EN 13743:2002)
- Safety requirements for diamond blades (EN 13236: 2001).

Thus the oSa symbol on the abrasive signifies enhanced application safety for the user, a reduced liability risk and excellent brand image for manufacturers, traders and those in marketing.

ISO9001, certifies Quality Management system is in accordance with requirements of quality standards.

ISO14001, certifies Environmental Management system is in accordance with requirements of environmental standards.

OHSAS18001, health and safety at work certification.





UNDERSTANDING THE FLEXOVIT PRODUCT RANGE

The new product line uses the powerful Flexovit yellow and iconic 'O' symbol to give impact and recognition in the merchandising environment.

This style is applied throughout the whole range with simple and direct communication using illustrations and icons supported where needed by text in eight European languages for easy product selection.

Flexovit and Flexovit PRO

There are two levels of product performance within the range – Flexovit and Flexovit PRO. The majority of the range are standard quality products with a good level of performance. Flexovit PRO products have additional premium attributes giving more advanced and professional performance levels.



PRO is synonymous with professional:

- Better quality product
- For the PRO DIY'er and professional tradesmen
- Professional performance.

All PRO products feature a PRO logo and a PRO attribute which explains the performance benefit.



LONGER LIFE

Within coated abrasives longer life PRO products are generally manufactured from aluminium oxide, combined with either a heavy paper or cloth backing material. This makes them incredibly durable and long lasting.

For diamond blades the products have a laser welded segmented rim with 10mm high segments which give extended product life.

PRO cutting off and grinding wheels have an advanced specification that gives them extended product life.

All Flexovit Merchandising PRO products with longer life attributes are ideal for more demanding applications or where regular product use is required.



STRONGER

The strongest backing material in the coated abrasives range is cloth. Cloth backed products such as Emery Cloth Sheets are extremely strong, incredibly durable, and can be torn into strips for hand sanding the toughest metal applications.



FLEXIBLE

Flexibility is a significant benefit when sanding contoured surfaces and hard to reach areas. The soft, absorbent, flexible nature of non woven abrasive pads makes them ideal for sanding such demanding surfaces.



SMOOTHER FINISH

A smooth, blemish free surface is essential to achieve a 'glass like' finish. Flexovit PRO products are manufactured using silicon carbide abrasive combined with a very unique stearate or 'liquid soap' coating. This significantly improves performance and finish by reducing friction and giving a gliding sanding action which results in a very consistent scratch free surface.




PRECISION CUTTING

When cutting any material the quality of the cut is extremely important as rough edges appear messy, unfinished and suggest poor quality. With Flexovit PRO Precision Cutting Diamond Blades there is significantly less chance of any chipping, burrs, or burn and the increased accuracy and thinner blades means they are much easier to use. Also less heat and dust is generated as a lower proportion of the wheel is in direct contact with the workpiece – resulting in a much cleaner, more precise cut.

Packaging Communication

Each pack has one 'lead illustration' showing power tool type or a hand use application. A second illustration shows which materials the product can be used on (for example wood or metal). This is then supported by secondary information such as technical data.





UNDERSTANDING THE FLEXOVIT PRODUCT RANGE (cont)

Differentiation Within The Ranges

Where greater differentiation is needed within a range colour coding and application illustrations are used.




Technical Information

The technical information box contains the following information where needed:




Grit Size Speed Wet / Dry Quantity Machine type diagrams Product diagram Power tool brands

On the back of the packaging are two charts translated into 8 European languages showing PRO attributes and grit scales.



PICTOGRAMS

Below is an explanation of all the pictograms appearing within the Flexovit range.







MERCHANDISING OPTIONS

There are two types of packaging format within the range, each bringing unique benefit:



Retail Packaging (Prepack)

These contain smaller quantities and are designed for merchandising from hooks within a display unit.

The packaging quantities and packaging format are ideal for the DIY market.



Shelf-Ready Trade Packaging (Bulk) This range contains higher pack quantities and is designed to target semi-professionals within DIY, Hardware, Builders Merchants, Painting and Decorating sectors and Industrial-retail.

These consist of shrink-wrapped products shipped and displayed within 'shelf-ready' merchandising boxes.

Point Of Purchase

Flexovit brings a new, innovative and dynamic Point Of Purchase merchandising programme which:

- · creates impact and presence for the Flexovit brand
- demonstrates an integrated & complete product category
- creates an overall impression and through visual clues: informs, educates and 'tells a story'
- saves time reduces time spent selecting the right product

Provides category impact, ease of shop, better informed decisions which result in higher basket values = **increased abrasive category profitability & revenue.**



Ask your Local Sales or Customer Service Representative about the Flexovit POP programme.





CUTTING-OFF AND GRINDING WHEELS

- 14 Useful Information
- 16 Cutting-Off Wheels
- 20 Grinding Wheels



USEFUL INFORMATION

Flexovit offers an extensive range of professional high performance wheels suitable for cutting and grinding a wide variety of materials, including steel, stainless steel and stone – with a full range of sizes for angle grinders, petrol saws, chop saws and fixed machines up to and including 400mm diameter.

SELECTING THE RIGHT PRODUCT

Flexovit Cutting and Grinding Wheels come in a range of sizes from 100mm to 230mm for use on portable angle grinders, and 300mm to 400mm for use on petrol saws, chop saws and stationary machines. They are available in 3 different types, 27, 41, and 42. All Type 27 wheels should be used for grinding whilst all type 41 and 42 wheels should be used for cutting. The wheel type can be easily identified by the following pictograms which appear next to the tables in the catalogue as well as on the products themselves.

Grinding Type 27 Wheels (BF 27)

Cutting Type 41 Wheels (BF 41)

Type 42 Wheels (BF 42)

MACHINE GUIDE

Flexovit Cutting-Off and Grinding Wheels are designed for use on a wide variety of machines. The relevant machine types are easily identified by the following pictograms that are contained both in the catalogue tables and on the product itself.







Petrol Saw



Stationery Saw

MATERIAL APPLICATION GUIDE

Flexovit cutting and grinding wheels can be used on a wide range of materials – each material is easily identified and differentiated by the colour of the wheel.



Steel/Inox



Multi-Purpose


T

Steel



Stone

UNDERSTANDING THE PRODUCT



* Speed Stripe Key

Do not operate your Flexovit cutting or grinding wheel at a speed greater than that as indicated by the colour of the speed stripe.



DIFFERENTIATION WITHIN THE RANGE

Where greater differentiation is needed within a range, this is done through colour coding and application instructions.







CUTTING-OFF WHEELS





TYPE 41

STEEL INOX CUTTING-OFF WHEELS

A 46 S-BF41 Pro

A 46 S-BF41 Pro

Ultra long life

Dimensions (mm) DxTxB 115x1.0x22.2 115x1.6x22.2 125x1.0x22.2 125x1.6x22.2

180x1.6x22.2

230x1.9x22.2

• Thin accurate cutting

• Free from Iron, Sulphur, and Chlorine

- · Comfortable and easy to use
- Straight an
- Thin accura
- Free from li

nd fast cutting rate cutting Iron, Sulphur, and Chlorine TYPE 41				41
;	Specification	Quantity per Case	Article No.	Barcode
	A 60 S-BF41 Pro	25	66252920407	8711479388606
!	A 46 S-BF41 Pro	25	66252920408	8711479388620
	A 60 S-BF41 Pro	25	66252920409	8711479388644
1	A 46 S-BF41 Pro	25	66252920410	8711479388668

25

25

0

66252920411

66252920412






8711479388682

8711479388705

Dimensions	Specification	Quantity	Article No.	Barcode
(mm) DxTxB		per Case		
115x1.0x22.2	A 60 R-BF41	25	66252920421	8711479388897
115x1.6x22.2	A 46 R-BF41	25	66252920422	8711479388910
125x1.0x22.2	A 60 R-BF41	25	66252920423	8711479388934
125x1.6x22.2	A 46 R-BF41	25	66252920424	8711479388958
150x1.6x22.2	A 46 R-BF41	25	66252920425	8711479388972
180x1.6x22.2	A 46 R-BF41	25	66252920426	8711479388996
230x1.9x22.2	A 46 R-BF41	25	66252920427	8711479389016





TYPE 41

MULTI-PURPOSE CUTTING-OFF WHEELS


- Cuts all materials; Steel, PVC, Stone, INOX, and Tiles
- Comfortable and easy to use
- Cool precise cutting



Dimensions (mm) DxTxB	Specification	Quantity per Case	Article No.	Barcode
115x1.0x22.23	C 46 R-BF41	25	66252926775	8711479427732
115x1.6x22.23	C 46 R-BF41	25	66252920428	8711479389030
125x1.0x22.23	C 46 R-BF41	25	66252926776	8711479427749
125x1.6x22.23	C 46 R-BF41	25	66252920429	8711479389054
150x1.6x22.23	C 46 R-BF41	25	66252926777	8711479427756
180x1.6x22.23	C 46 R-BF41	25	66252926778	8711479427763
230x1.9x22.23	C 46 R-BF41	25	66252926779	8711479427787

STEEL CUTTING-OFF WHEELS

- Comfortable and easy to use
- Straight clean cutting



TYPE 41

			ŦI		
	Dimensions (mm) DxTxB	Specification	Quantity per Case	Article No.	Barcode
	100x2.5x16.0	A 24 R-BF41	25	66252920432	8711479389115
	115x2.0x22.23	A 24 R-BF41	25	66252920430	8711479389078
	115x3.2x22.23	A 24 R-BF41	25	66252920438	8711479389238
	125x2.0x22.23	A 24 R-BF41	25	66252920431	8711479389092
	125x3.2x22.23	A 24 R-BF41	25	66252920439	8711479389252
	150x2.5x22.23	A 24 R-BF41	25	66252920435	8711479389177
	180x3.2x22.23	A 24 R-BF41	25	66252920440	8711479389276
	230x2.5x22.23	A 24 R-BF41	25	66252925643	8711479425035
	230x3.2x22.23	A 24 R-BF41	25	66252920441	8711479389290



STEEL CUTTING-OFF WHEELS FOR 80 m/s CHOP SAWS


- Quick cool cutting
- Burn and burr free results

				TYPE 41		
	Dimensions (mm) DxTxB	Specification	Quantity per Case	Article No.	Barcode	
	300x2.8x25.4	A 24 R-BF41	10	66252920471	8711479389979	
	350x3.0x25.4	A 24 R-BF41	10	66252920472	8711479389993	
	400x3.0x25.4	A 24 R-BF41	10	66252920473	8711479390012	



STEEL CUTTING-OFF WHEELS FOR 80 m/s PETROL SAWS

- Quick cool cutting
- Burn and burr free results





			TYPE 4	1
Dimensions (mm) DxTxB	Specification	Quantity per Case	Article No.	Barcode
300x3.5x20.0	A 24 R-BF41	10	66252920467	8711479389894
300x3.5x22.2	A 24 R-BF41	10	66252920468	8711479389917



· Quick cool cutting


• Burn and burr free results



			TYPE 41		
Dimensions (mm) DxTxB	Specification	Quantity per Case	Article No.	Barcode	
300x3.5x25.4	A 24 R-BF41	10	66252920474	8711479390036	
350x3.5x25.4	A 24 R-BF41	10	66252920475	8711479390050	

STONE CUTTING-OFF WHEELS

- Straight fast cutting
- · Comfortable and easy to use
- No loading or glazing of the wheel



			TYPE 4	1
Dimensions (mm) DxTxB	Specification	Quantity per Case	Article No.	Barcode
100x2.5x16.0	C 24 R-BF41	25	66252920452	8711479389566
115x2.5x22.2	C 24 R-BF41	25	66252920453	8711479389580
125x2.5x22.2	C 24 R-BF41	25	66252920454	8711479389603
150x2.5x22.2	C 24 R-BF41	25	66252920455	8711479389627
180x2.5x22.2	C 24 R-BF41	25	66252920456	8711479389641
230x2.5x22.2	C 24 R-BF41	25	66252920457	8711479389665





- Straight fast cutting
- Comfortable and easy to use

 No loading or gla 	zing of the wheel		TYPE 4	1
Dimensions (mm) DxTxB	Specification	Quantity per Case	Article No.	Barcode
300x3.5x20.0	C 24 R-BF41	10	66252920469	8711479389931
300x3.5x22.2	C 24 R-BF41	10	66252920470	8711479389955


0



 Ultra long life Comfortable Fast cutting 	DX CUTTING-O e and easy to use n, Sulphur, and Chlorin		LS OIL	42
Dimensions (mm) DxTxB	Specification	Quantity per Case	Article No.	Barcode
100x3.2x16.0	A 24 S-BF42 Pro	25	66252924041	8711479417832
115x3.2x22.2	A 24 S-BF42 Pro	25	66252920413	8711479388729
125x3.2x22.2	A 24 S-BF42 Pro	25	66252920414	8711479388743
180x3.2x22.2	A 24 S-BF42 Pro	25	66252920415	8711479388767
230x3.2x22.2	A 24 S-BF42 Pro	25	66252920416	8711479388781

STEEL CUTTING-OFF WHEELS

- Comfortable and easy to use
- Straight clean cutting




fiex vit
Mar Conce

Straight cicant	cutting			
			TYPE	42
Dimensions (mm) DxTxB	Specification	Quantity per Case	Article No.	Barcode
115x2.5x22.2	A 24 R-BF42	25	66252920433	8711479389139
115x3.2x22.2	A 24 R-BF42	25	66252920442	8711479389313
125x2.5x22.2	A 24 R-BF42	25	66252920434	8711479389153
125x3.2x22.2	A 24 R-BF42	25	66252920443	8711479389337
180x2.5x22.2	A 24 R-BF42	25	66252920436	8711479389191
180x3.2x22.2	A 24 R-BF42	25	66252920444	8711479389351
230x2.5x22.2	A 24 R-BF42	25	66252920437	8711479389214
230x3.2x22.2	A 24 R-BF42	25	66252920445	8711479389375

STONE CUTTING-OFF WHEELS

- Straight fast cutting
- Comfortable and easy to use
- No loading or glazing of the wheel









GRINDING WHEELS






STEEL INOX GRINDING WHEELS

• Ultra long life

TYPE 27

- Fast stock removal
- Comfortable and easy to use
- Free from Iron, Sulphur, and Chlorine





uantity er Case	Article No.	Barcode
10	66252924042	8711479417849
10	66252920417	8711479388804
10	66252920418	8711479388828
10	66252920419	8711479388842
10	66252920420	8711479388866


STEEL GRINDING WHEELS

Efficient

Dimensions

(mm) DxTxB


- Fast stock removal
- Comfortable and easy to use



TYPE 27 Specification Quantity Article No. Barcode per Case A 24 R-BF27 66252920446 8711479389399 10 10 A 24 R-BF27 66252920447 8711479389412 A 24 R-BF27 10 66252920448 8711479389436 A 24 R-BF27 10 66252920449 8711479389450 A 24 R-BF27 10 66252920450 8711479389474 A 24 R-BF27 10 66252920451 8711479389542

STONE GRINDING WHEELS

- Fast stock removal
- Comfortable and easy to use
- No loading or glazing of the wheel






	Dimensions (mm) DxTxB	Specification	Quantity per Case	Article No.	Barcode
	100x6.5x16.0	C 24 R-BF27	10	66252920462	8711479389764
	115x6.5x22.2	C 24 R-BF27	10	66252920463	8711479389788
_	125x6.5x22.2	C 24 R-BF27	10	66252920464	8711479389801
/	180x6.5x22.2	C 24 R-BF27	10	66252920465	8711479389825
	230x6.5x22.2	C 24 R-BF27	10	66252920466	8711479389849







BONDED ABRASIVES

- 22 Useful Information
- 24 Sharpening Stones
- 25 Mounted Points
- 26 Vitrified Bench Wheels



USEFUL INFORMATION

Flexovit offers a unique range of professional bonded abrasives that meet the requirements of any merchandising environment. The range includes vitrified grinding wheels, sharpening stones and mounted points which are all suitable for general maintenance applications.

SELECTING THE RIGHT PRODUCT

Vitrified Bench Grinding Wheels

Increasingly today's tools are made from hard, tough and difficult to grind steel. Flexovit Vitrified bench grinding wheels are manufactured from Aluminium Oxide, which is ideal for grinding all types of steel and tool sharpening. The wheels range in dimension and are available in 2 grits; 36 grit for stock removal and 60 grit for sharpening.

Sharpening Stones

Each Flexovit sharpening stone is specifically designed for different blade sharpening applications encountered in the home, garden, or workshop. All sharpening stones are manufactured from aluminium oxide. This type of abrasive is effective at grinding all types of steel and it is especially suited to sharpening as it requires minimal grinding pressure.

The Flexovit knife sharpener is a unique product to Saint-Gobain Abrasives and is the ideal accessory for any kitchen. It is extremely effective and can increase the performance of all kitchen knives. It is also easy to use and compact for convenient storage in any kitchen drawer.


Mounted Points

Flexovit mounted points are made from pink aluminium oxide and are ideal for cleaning tasks on metal, stone, ceramic and plastic. They can also be used for deburring curved workpieces and internal grinding. All mounted points feature 6mm spindles which can be used in most electric drills.



Flexovit vitrified bench wheels, sharpening stones and mounted points are manufactured from pink and white aluminium oxide which are friable free cutting abrasives that require minimal grinding pressure. They are ideal for grinding high alloyed types of steel as they are more brittle than other types of aluminium oxide. They also provide significant advantages when grinding harder materials.

UNDERSTANDING THE PRODUCT



BONDED ABRASIVES - USEFUL INFORMATION





SHARPENING STONES



SHARPENING STONE

FOR SHARPENING GARDEN TOOLS

Aluminium Oxide abrasive for long lasting sharp edges on garden tools

Ideal for sharpening garden tools and blades

Dimensions (mm) HxWx		Quantity per Pack	Packs per Case	Article No.	Barcode
100x19x6	Fine	1	10	66243441050	3157625562196





flex

7

SHARPENING STONE

FOR SHARPENING CURVED GENERAL TOOLS

- Aluminium Oxide abrasive for long lasting sharp edges on curved general tools
- Ideal for sharpening curved tools, scissors, knives and other blades

Dimensions (mm) HxWxT	Grade	Quantity per Pack	Packs per Case	Article No.	Barcode
115x45x10	Medium	1	10	66243439334	3157625561908





SHARPENING STONE FOR SHARPENING KITCHEN AND GENERAL TOOLS

 Aluminium Oxide abrasive for long lasting sharp edges on kitchen and general tools

• Ideal for sharpening kitchen knives, scissors and other blades

Dimensions (mm) HxWxT	Grade	Quantity per Pack	Packs per Case	Article No.	Barcode
125x50x19	Coarse / Fine	1	10	66243439333	3157625561915

SHARPENING STONE

FOR SHARPENING HEAVY DUTY GARDEN TOOLS

- Aluminium Oxide abrasive for long lasting sharp edges on heavy duty garden tools
- Ideal for sharpening scythes, sickles and garden shears

Dimensions (mm) HxWxT	Grade	Quantity per Pack	Packs per Case	Article No.	Barcode
240x35x13	Fine	1	10	66243440255	3157625561922



KNIFE SHARPENER

- KNIFE SHARPENINGAluminium Oxide abrasive for long lasting sharp edges on kitchen knives
- Ideal for sharpening kitchen knives

Quantity per Pack	Packs per Case	Article No.	Barcode
1	12	66243444047	3157625566668

MOUNTED POINTS



MOUNTED POINTS

- Aluminium Oxide abrasive
- 6mm spindle
- Ideal for precision grinding of steels and alloy steels



				A12	W204 A25
Dimensions (mm)	Grade	Quantity per Pack	Packs per Case	Article No.	Barcode
6mm spindle	Fine	3	5	66243439327	3157625561793

BONDED ABRASIVES - SHARPENING STONES/MOUNTED POIN





VITRIFIED BENCH WHEELS



VITRIFIED BENCH WHEELS

- Aluminium Oxide abrasive
- Suitable for grinding all types of steel
- For use on bench or pedestal grinders
- Reduction rings are included to adapt products to different sized spindles (25mm/20mm, 32mm/25mm)



Dimensions (mm) DxTxB	Grit	Application	Max rpm / m/s	Quantity per Pack	Packs per Case	Article No.	Barcode
125x16x32	60	Precision Grinding	5438 rpm or 35 m/s	1	1	66243439313	3157625560598
125x16x32	36	Rough Grinding	5438 rpm or 35 m/s	1	1	66243439310	3157625561823
150x20x32	60	Precision Grinding	4459 rpm or 35 m/s	1	1	66243439317	3157625561762
150x20x32	36	Rough Grinding	4459 rpm or 35 m/s	1	1	66243439315	3157625561755
200x25x32	60	Precision Grinding	3344 rpm or 35 m/s	1	1	66243439320	3157625561786
200x25x32	36	Rough Grinding	3344 rpm or 35 m/s	1	1	66243439319	3157625561779





COATED ABRASIVES

- 28 Useful Information
- 30 Hand Sanding Sheets
- 35 Sanding Rolls 5M
- 37 Orbital Sheets
- 40 Sanding Discs
- 44 Multi Sanding Sheets
- 46 Sanding Belts
- 50 Sanding Block Kits and Sponges



USEFUL INFORMATION

The extensive range of Flexovit's coated product line has been developed to provide highly effective sanding solutions for all requirements encountered in a merchandising environment.

This good quality product line is supported by a selection of PRO products that give advanced performance, often required by more demanding applications.

UNDERSTANDING THE PRODUCT

Constant grey background (when colour coding is not required) Constant brand colour throughout the Flexovit range flex Ovit PRO Flexovit branding - reinforced with the PRO logo gives superior split colour through the products immediate centre of the Flexovit O shelf presence differentiating them Lead illustration within the range immediately communicates the Suitable materials are product type and communicated at a its hand sanding or glance through a range power tool application of pictograms 36 ØIISm 3x 0 Product window enables The second Size, grit, consumers to touch the product, quality product and test the grit The PRO icon displays a pictogram demonstrating the performance benefit of any PRO products within the range

DIFFERENTIATION WITHIN THE RANGE

Where greater differentiation is needed within a range, such as Hand Sanding Sheets, this is done through colour coding and application instructions.



SELECTING THE RIGHT PRODUCT

Colour coding and specific application illustrations are used to differentiate between product types and to make product selection easier.

Glasspaper

Economy hand sanding sheets are ideal for general purpose applications.



General Purpose Aluminium Oxide Paper

This tough and sharp aluminium oxide with an open coat structure is ideal for general purpose sanding and stock removal.



High Performance Aluminium Oxide Paper

The tough and sharp aluminium oxide combined with a heavy paper backing makes this product extremely durable, long lasting, and ideal for either hand sanding or power tool use.

films	0.4	1
		0
東公園	1999	9

Waterproof Paper

A sharp silicon carbide with a closed coat structure makes this paper ideal for finishing. Waterproof Paper is specially treated making it ideal for use with water. The paper lasts longer and gives a smoother finish when used wet as the water cleans, lubricates and helps prevent clogging.

flex (vit 🞫	
2	0	
4		9

Finishing Paper

A silicon carbide abrasive featuring a unique and innovative stearate coating. This significantly improves performance and finish by reducing friction and clogging giving a gliding sanding action which results in a very consistent scratch free surface.



Emery Cloth Sheets

A high performance emery abrasive cloth for fast and aggressive removal of paint, rust and rough surfaces. The fast cutting emery is backed with a heavy twill cloth, which allows the sheet to be torn into strips, giving superb flexibility for working on contoured or flat surfaces.



Aluminium Oxide Fibre Discs

A tough and sharp aluminium oxide combined with a dense semi-rigid backing gives this product extremely long life. It is ideal for working on metal using an angle grinder.



Aluminium Oxide Cloth

A tough and sharp aluminium oxide combined with a cloth backing giving maximum strength and flexibility, making it ideal for aggressive sanding with belt sanders.



Non-Woven Abrasive

These products are designed for finishing applications where light stock removal is required. The unique qualities make them extremely flexible for working on contoured surfaces. The products can be used with water and can also be washed and reused. Available in 1/3 sheet size and for use either by hand or with orbital sanders.



Sanding Sponges

Designed for sanding contoured, flat and hard to reach areas, the double-sided dual grit abrasive sponges feature hard wearing aluminium oxide which makes them very durable and long lasting. The sponges are washable, therefore reusable – simply rinse in water to remove 'clogging'. Available in 3 types; standard, large, and double angled.



Sanding Block Kits

Sanding block kits contain an assortment of aluminium oxide sheets and a sanding block. The blocks are very comfortable to use and those featuring a hook and loop backing system allow for quick and easy sheet changing.





HAND SANDING SHEETS



GLASS PAPER SHEETS

- Economy paper sheets
- Suitable for hand use



PREPACK						
Dimensions (mm) WxL	Grade		Quantity per Pack	Packs per Case	Article No.	Barcode
230x280	Fine		4	50	63642526249	3157625529861
230x280	Medium		4	50	63642526259	3157625529892
230x280	Coarse		4	50	63642526292	3157625529908
230x280	Assorted	1xcoarse 2xmedium 1xfine	4	50	63642526485	3157625530843



TRADE P/	ACK					
Dimensions (mm) WxL	Grade		Quantity per Pack	Packs per Case	Article No.	Barcode
230x280	Fine		15	15	63642526530	3157625537781
230x280	Medium		15	15	63642526538	3157625537798
230x280	Coarse		15	15	63642526541	3157625537804
230x280	Assorted	5xcoarse 10xmedium 10xfine	25	10	63642526563	3157625537811



SEMI BUL	K				
Dimensions (mm) WxL	Grade	Quantity per Pack	Packs per Case	Article No.	Barcode
230x280	0	25	5	63642558231	5010352582319
230x280	0	25	5	63642558232	5010352582326
230x280	1	25	5	63642558233	5010352582333
230x280	1.5	25	5	63642558234	5010352582340
230x280	F2	25	5	63642558235	5010352582357
230x280	M2	25	5	63642558236	5010352582364
230x280	S2	25	5	63642558237	5010352582371
230x280	2.5	25	5	63642558238	5010352582388
230x280	3	25	5	63642558239	5010352582395
230x280 230x280 230x280	M2 S2 2.5	25 25 25	5 5 5	63642558236 63642558237 63642558238	501035258236 501035258237 501035258238



30



GENERAL PURPOSE SHEETS

General Purpose Aluminium Oxide for use on

a variety of surfaces • Suitable for hand or power tool use



PREPACK						
Dimensions (mm) WxL	Grade	Grit	Quantity per Pack	Packs per Case	Article No.	Barcode
230x280	Fine	120	3	25	63642526254	3157625529885
230x280	Medium	80	3	25	63642526251	3157625529878
230x280	Coarse	50	3	25	63642526238	3157625529854
230x280	Assorted	1x50 1x80 1x120	3	25	63642526482	3157625530836



I KADE PA	icn					
Dimensions (mm) WxL	Grade	Grit	Quantity per Pack	Packs per Case	Article No.	Barcode
230x280	Fine	120	15	15	63642526525	3157625537767
230x280	Medium	80	15	15	63642526524	3157625537743
230x280	Coarse	50	15	15	63642526522	3157625537736
230x280	Assorted	5x50 10x80 10x120	25	10	63642526527	3157625537774



HIGH PERFORMANCE SHEETS

- Tough & durable heavy paper backing for longer product life
- · High performance Aluminium Oxide for use on a variety of surfaces

10x80 10x120

• Suitable for hand or power tool use

PREPACK



	Dimensions (mm) WxL	Grade	Grit	Quantity per Pack	Packs per Case	Article No.	Barcode
)	230x280	Fine	120	3	10	63642526313	3157625530058
	230x280	Medium	80	3	10	63642526312	3157625530041
	230x280	Coarse	50	3	10	63642526311	3157625530034
	TRADE PA	ACK					
	Dimensions (mm) WxL	Grade	Grit	Quantity per Pack	Packs per Case	Article No.	Barcode
		Grade Fine	Grit 120			Article No. 63642526593	Barcode 3157625537996
the of the	(mm) WxL			per Pack	per Case		
a an a an	(mm) WxL 230x280	Fine	120	per Pack	per Case 15	63642526593	3157625537996

COATED ABRASIVES – HAND SANDING SHEETS





EMERY CLOTH SHEETS

- Incredibly strong cloth backing for increased product strength and durability
- For removing rust, paint, and scale from metal surfaces
- Fine grits also ideal for preparing and polishing metal
- Product can be torn into strips for detailed work
- Suitable for hand or power tool use



PREPACK						
Dimensions (mm) WxL	Grade	Grit	Quantity per Pack	Packs per Case	Article No.	Barcode
230x280	Fine		3	15	63642526306	3157625530003
230x280	Medium		3	15	63642526304	3157625529991
230x280	Coarse		3	15	63642526308	3157625530027
230x280	Assorted	1xcoarse 1xmedium 1xfine	3	15	63642526493	3157625530881



TRADE PACK								
Dimensions (mm) WxL	Grade	Grit	Quantity per Pack	Packs per Case	Article No.	Barcode		
230x280	Fine		15	10	63642526582	3157625537934		
230x280	Medium		15	10	63642526583	3157625537941		
230x280	Coarse		15	10	63642526584	3157625537958		
230x280	Assorted	5xcoarse 10xmedium 10xfine	25	8	63642526589	3157625537965		
SEMI BUI	K							



SEIVII DULK	L				
Dimensions (mm) WxL	Grit	Quantity per Pack	Packs per Case	Article No.	Barcode
230x280	150	25	5	63642558253	5010352582531
230x280	120	25	5	63642558252	5010352582524
230x280	100	25	5	63642558251	5010352582517
230x280	80	25	5	63642558250	5010352582500
230x280	60	25	5	63642558249	5010352582494
230x280	40	25	5	63642558248	5010352582487



WATERPROOF PAPER SHEETS

• Can be used wet or dry

- Highly flexible high quality silicon carbide abrasive
- · Ideal for use with water or other lubricants



PREPACK						
Dimensions (mm) WxL	Grade	Grit	Quantity per Pack	Packs per Case	Article No.	Barcode
230x280	Fine	400	3	25	63642526303	3157625529984
230x280	Medium	240	3	25	63642526302	3157625529977
230x280	Coarse	180	3	25	63642526301	3157625529953
230x280	Assorted	1x180 1x240 1x400	3	25	63642526491	3157625530874



I KADE PF	ACK					
Dimensions (mm) WxL	Grade	Grit	Quantity per Pack	Packs per Case	Article No.	Barcode
230x280	Fine	400	15	15	63642526580	3157625537903
230x280	Medium	240	15	15	63642526579	3157625537897
230x280	Coarse	180	15	15	63642526577	3157625537873
230x280	Assorted	5x180 10x240 10x400	25	10	63642526581	3157625537927



V-cdC	SEMI BULI	K				
21.12	Dimensions (mm) WxL	Grit	Quantity per Pack	Packs per Case	Article No.	Barcode
1911	230x280	1000	25	5	63642558246	5010352582463
5	230x280	800	25	5	63642558245	5010352582456
100	230x280	600	25	5	63642558244	5010352582449
	230x280	400	25	5	63642558243	5010352582432
	230x280	320	25	5	63642558242	5010352582425
	230x280	240	25	5	63642558241	5010352582418
	230x280	150	25	5	63642558240	5010352582401



NON WOVEN ABRASIVE PADS

- Highly flexible for detailed sanding
- Can be washed and reused
- Ideal for use wet, dry or with a chemical stripper
- · Can be used on a range of applications including heavy duty cleaning, finishing, and light polishing
- · Suitable for hand or power tool use



Dimensions (mm) WxL	Grade	Quantity per Pack	Packs per Case	Article No.	Barcode
115x280	Fine	1	10	63642527470	3157625554153
115x280	Medium	1	10	63642527517	3157625554177
115x280	Coarse	1	10	63642527522	3157625554184







FINISHING PAPER SHEETS

- Ideal for fine finishing and between coats sanding
- High quality extremely sharp silicon carbide abrasive
- Stearate coating reduces clogging
- · Ideal to achieve a very smooth surface

PREPACK



Dimensions (mm) WxL	Grade	Grit	Quantity per Pack	Packs per Case	Article No.	Barcode
230x280	Fine	240	3	25	63642526300	3157625529946
230x280	Medium	180	3	25	63642526299	3157625529939
230x280	Coarse	120	3	25	63642526294	3157625529915
230x280	Extra Coarse	80	3	25	63642526296	3157625529922
230x280	Assorted	1x120 1x180 1x240	3	25	63642526488	3157625530867



TRADE P	ACK					
Dimensions (mm) WxL	Grade	Grit	Quantity per Pack	Packs per Case	Article No.	Barcode
230x280	Fine	240	15	15	63642526573	3157625537859
230x280	Medium	180	15	15	63642526569	3157625537842
230x280	Coarse	120	15	15	63642526568	3157625537835
230x280	Extra Coarse	80	15	15	63642526567	3157625537828
230x280	Assorted	5x120 10x180 10x240	25	10	63642526576	3157625537866

SANDING ROLLS



GENERAL PURPOSE ROLLS

- General Purpose Aluminium Oxide for use on a variety of surfaces
- Suitable for hand or power tool use



Dimensions (mm x m) WxL	Grade	Grit	Quantity per Case	Article No.	Barcode
115x5	Fine	180	6	63642526413	3157625530522
115x5	Medium	120	6	63642526412	3157625530515
115x5	Coarse	80	6	63642526411	3157625530508
115x5	Extra Coarse	50	6	63642526410	3157625530492
Dimensions (mm x m) WxL	Grade	Grit	Quantity per Case	Article No.	Barcode
	Grade Medium	Grit 120		Article No. 69957398441	Barcode 3157625749931
(mm x m) WxL			per Case		
(mm x m) WxL 115x10	Medium	120	per Case	69957398441	3157625749931

TRADE PERFORMANCE ROLLS

- Trade quality aluminium oxide for use on a variety of surfaces
- Durable paper backing for hand or power tool use




Dimensions (mm x m) WxL	Grade	Grit	Quantity per Case	Article No.	Barcode
115x5	Fine	120	10	63642569921	3157625581449
115x5	Medium	80	10	63642569918	3157625581418
115x5	Coarse	60	10	63642569915	3157625581388
115x5	Extra Coarse	40	10	63642569909	3157625581333
Dimensions (mm x m) WxL	Grade	Grit	Quantity per Case	Article No.	Barcode
115x10	Fine	120	10	63642569922	3157625581456
115x10	Medium	80	10	63642569919	3157625581425
115x10	Coarse	60	10	63642569916	3157625581395
115x10	Extra Coarse	40	10	63642569912	3157625581364
Dimensions (mm x m) WxL	Grade	Grit	Quantity per Case	Article No.	Barcode
115x50	Fine	120	1	63642569923	3157625581463
115x50	Medium	80	1	63642569920	3157625581432
115x50	Coarse	60	1	63642569917	3157625581401
115x50	Extra Coarse	40	1	63642569914	3157625581371







HIGH PERFORMANCE ROLLS







PRO

Suitable for hand					
Dimensions (mm x m) WxL	Grade	Grit	Quantity per Case	Article No.	Barcode
115x5	Fine	120	6	63642526430	3157625530614
115x5	Medium	80	6	63642526429	3157625530607
115x5	Coarse	60	6	63642526423	3157625530591
115x5	Extra Coarse	40	6	63642526421	3157625530584



- Ideal for fine finishing and between coats sanding
- High quality extremely sharp silicon carbide abrasive
- Stearate coating reduces clogging
- Ideal to achieve a very smooth surface




Dimensions (mm x m) WxL	Grade	Grit	Quantity per Case	Article No.	Barcode
115x5	Fine	320	6	63642526420	3157625530577
115x5	Medium	240	6	63642526417	3157625530553
115x5	Coarse	180	6	63642526416	3157625530546
115x5	Extra Coarse	120	6	63642526415	3157625530539



EMERY CLOTH HANDY ROLLS

- Incredibly strong cloth backing for increased product strength and durability
- For removing rust, paint and scale from metal · Size ideal for detailed work, such as plumbing projects



Dimensions (mm x m) WxL	Grade	Quantity per Case	Article No.	Barcode
38x5	Fine	6	69957389879	8711479423611
38x5	Medium	6	69957389877	8711479423598
38x5	Coarse	6	69957389874	8711479423567



ORBITAL SHEETS



QUICK RELEASE ORBITAL SHEETS

- High performance aluminium oxide for use on a variety of surfaces
- Hook and loop backing allows quick and easy orbital changing



P	PREPACK								
	mensions nm) WxL	Grade	Grit	Quantity per Pack	Packs per Case	Article No.	Barcode		
		Very Fine	180	6	5	69957389802	8711479421334		
_	3x185	Fine	120	6	5	69957389801	8711479421327		
	••••	Medium	80	6	5	69957389800	8711479421303		
		Coarse	50	6	5	69957389786	8711479421167		
Ma	Machine Brand BLACK & DECKER, PEUGEOT								

Dimensions (mm) WxL	Grade	Grit	Quantity per Pack	Packs per Case	Article No.	Barcode	
93x185	Fine	120	6	5	63642526345	3157625530218	
	Medium	80	6	5	63642526344	3157625530201	
•••	Coarse	50	6	5	63642526342	3157625530195	
Machina Prand PLACK & DECKED DELICEOT							

Machine Brand BLACK & DECKER, PEUGEOT



TRADE PACK							
Dimensions (mm) WxL	Grade	Grit	Quantity per Pack	Packs per Case	Article No.	Barcode	
	Fine	120	15	12	63642526673	3157625538252	
93x185	Medium	80	15	12	63642526672	3157625538245	
•••	Coarse	50	15	12	63642526670	3157625538238	
••••	Assorted	5x50 10x80 10x120	25	8	63642526674	3157625538269	
Machine Bra	nd BLACK 8	& DECKER, P	EUGEOT				



ORBITAL SHEETS

- High performance Aluminium Oxide for use
- on a variety of surfaces

PREPACK

• Available in a variety of sizes and dust hole configurations to fit most brands of orbital sander



Dimensions (mm) WxL	Grade	Grit	Quantity per Pack	Packs per Case	Article No.	Barcode
	Extra Fine	240	10	10	69957389773	3157625667136
93x230	Very Fine	180	10	10	69957389767	3157625667129
	Fine	120	10	10	63642526321	3157625530089
	Medium	80	10	10	63642526320	3157625530072
	Coarse	50	10	10	63642526314	3157625530065

Machine Brand AEG/ATLAS COPCO, BLACK & DECKER, BOSCH, CASALS, FESTO, HITACHI, MAKITA, METABO, PEUGEOT, RHINO, RYOBI, SKIL, STAYER

Dimensions (mm) WxL	Grade	Grit	Quantity per Pack	Packs per Case	Article No.	Barcode
	Very Fine	180	10	10	69957389783	8711479421129
93x230	Fine	120	10	10	63642526336	3157625530157
• • • •	Medium	80	10	10	63642526335	3157625530133
	Coarse	50	10	10	63642526330	3157625530126

Machine Brand BLACK & DECKER, BOSCH, CASALS, FESTO, MAKITA, METABO, RYOBI, SKIL

Dimensions (mm) WxL	Grade	Grit	Quantity per Pack	PacksAr per Case	ticle No.	Barcode
	Very Fine	180	10	10	69957389785	8711479421143
93x230	Fine	120	10	10	63642526341	3157625530188
• • • • •	Medium	80	10	10	63642526340	3157625530171
	Coarse	50	10	10	63642526337	3157625530164

Machine Brand AEG/ATLAS COPCO, BLACK & DECKER, CASALS, PEUGEOT, RHINO, STAYER

Dimensions (mm) WxL	Grade	Grit	Quantity per Pack	Packs per Case	Article No.	Barcode
	Very Fine	180	10	10	69957389775	3157625667143
115x280	Fine	120	10	10	63642526328	3157625530119
	Medium	80	10	10	63642526327	3157625530102
	Coarse	50	10	10	63642526326	3157625530096

Machine Brand AEG/ATLAS COPCO, BLACK & DECKER, BOSCH, CASALS, FESTO, HITACHI, MAKITA, METABO, PEUGEOT, RHINO, RYOBI, SKIL, STAYER

Dimensions (mm) WxL	Grade	Grit	Quantity per Pack	Packs per Case	Article No.	Barcode
	Very Fine	180	10	10	69957390011	8711479424991
115x280	Fine	120	10	10	63642526500	3157625530928
••••	Medium	80	10	10	63642526499	3157625530911
	Coarse	50	10	10	63642526498	3157625530904
Machine Brai			ER, BOSCH, CA	,		TI, FESTO, HITACHI,

Dimensions key: W = Width, L = Length



TRADE PA	ICK					
Dimensions (mm) WxL	Grade	Grit	Quantity per Pack	Packs per Case	Article No.	Barcode
	Fine	120	15	20	63642526603	3157625538047
93x230	Medium	80	15	20	63642526602	3157625538023
	Coarse	50	15	20	63642526597	3157625538016
	Assorted	5x50 10x80 10x120	25	10	63642526604	3157625538054
Machine Brar					CH, CASALS, FES , SKIL, STAYER	TO, HITACHI,
Dimensions (mm) WxL	Grade	Grit	Quantity per Pack	Packs per Case	Article No.	Barcode
	Fine	120	15	20	63642526613	3157625538122
93x230	Medium	80	15	20	63642526612	3157625538115
• • • •	Coarse	50	15	20	63642526610	3157625538108
• • • •	Assorted	5x50 10x80 10x120	25	10	63642526614	3157625538139
Machine Brand BLACK & DECKER, BOSCH, CASALS, FESTO, MAKITA, METABO, RYOBI, SKIL						
Dimensions (mm) WxL	Grade	Grit	Quantity per Pack	Packs per Case	Article No.	Barcode
	Fine	120	15	20	63642526625	3157625538177
93x230	Medium	80	15	20	63642526616	3157625538153
• • • •	Coarse	50	15	20	63642526615	3157625538146
• • •	Assorted	5x50 10x80 10x120	25	10	63642526627	3157625538184
Machine Brai	nd AEG/AT	LAS COPC	O, BLACK & [DECKER, CAS	SALS, PEUGEOT, F	RHINO, STAYER
Dimensions (mm) WxL	Grade	Grit	Quantity per Pack	Packs per Case	Article No.	Barcode
	Fine	120	15	20	63642526607	3157625538085
115x280	Medium	80	15	20	63642526606	3157625538078
	Coarse	50	15	20	63642526605	3157625538061
	Assorted	5x50 10x80 10x120	25	10	63642526608	3157625538092
Machine Brar					CH, CASALS, FES , SKIL, STAYER	TO, HITACHI,
Dimensions (mm) WxL	Grade	Grit	Quantity per Pack	Packs per Case	Article No.	Barcode
	Fine	120	15	20	63642526637	3157625538214
115x280	Medium	80	15	20	63642526635	3157625538207
••••	Coarse	50	15	20	63642526633	3157625538191
••••	Assorted	5x50 10x80 10x120	25	10	63642526639	3157625538221
Machine Bran			BOSCH, CAS			, FESTO, HITACHI,





SANDING DISCS



ECCENTRIC DISCS

• High performance Aluminium Oxide for use on a variety of surfaces



- Tough and durable backing for longer product life
- Hook and loop backing allows quick and easy disc changing
- Available in 3 sizes to fit most brands of eccentric sander



PREPACK							
Diameter (mm)	Grade	Grit	Quantity per Pack	Packs per Case	Article No.	Barcode	
	Extra Fine	240	6	10	69957389889	8711479422249	
	Very Fine	180	6	10	69957389888	8711479422232	
115	Fine	120	6	10	63642526386	3157625530324	
	Medium	80	6	10	63642526385	3157625530317	
	Coarse	50	6	10	63642526384	3157625530294	
	Assorted	2x50 2x80 2x120	6 D	10	63642526501	3157625530935	

Machine Brand BOSCH, EINHELL, KRESS, PEUGEOT, RYOBI, SKIL

Diameter (mm)	Grade	Grit	Quantity per Pack	Packs per Case	Article No.	Barcode
	Extra Fine	240	6	10	69957389891	8711479422263
	Very Fine	180	6	10	69957389890	8711479422256
125	Fine	120	6	10	63642526392	3157625530355
	Medium	80	6	10	63642526390	3157625530348
	Coarse	50	6	10	63642526387	3157625530331
	Assorted	2x50 2x80 2x120	6	10	63642526502	3157625530942
Machine Bra	nd AEG/ATI	LAS CO	PCO, BLACK	& DECKER, B	BOSCH, DEWALT, E	LU, FEIN, FESTO,

chine Brand AEG/AI LAS COPCO, BLACK & DECKER, BOSCH, DEWALI, ELU, FEIN, FES HITACHI, KRESS, MAKITA, METABO, RYOBI, SKIL

flex(vit
	1
50 000000 0.0000000000000000000000000000	

PREPACK										
Diameter (mm)	Grade	Grit	Quantity per Pack	Packs per Case	Article No.	Barcode				
	Extra Fine	240	6	10	69957389893	8711479422294				
	Very Fine	180	6	10	69957389892	8711479422287				
150	Fine	120	6	10	63642526397	3157625530386				
	Medium	80	6	10	63642526396	3157625530379				
	Coarse	50	6	10	63642526394	3157625530362				
	Assorted	2x50 2x80 2x120	6	10	63642526503	3157625530959				
Machine Bra	nd BOSCH,	DEWALT, E	LU, FELISAT	TI, FLEX, HITA	ACHI, IBREX PRO	TOOL, KRESS,				

METABO, PEUGEOT, STAYER



TRADE PACK									
Diameter (mm)	Grade	Grit	Quantity per Pack	Packs per Case	Article No.	Barcode			
	Fine	120	15	12	63642526704	3157625538351			
115	Medium	80	15	12	63642526703	3157625538344			
	Coarse	50	15	12	63642526702	3157625538337			
	Assorted	5x50 10x80 10x120	25	8	63642526705	3157625538368			
Machine Bran	d BOSCH,	EINHELL, K	RESS, PEUGE	EOT, RYOBI, S	SKIL				
Diameter (mm)	Grade	Grit	Quantity per Pack	Packs per Case	Article No.	Barcode			
	Fine	120	15	12	63642526709	3157625538399			
125	Medium	80	15	12	63642526708	3157625538382			
	Coarse	50	15	12	63642526707	3157625538375			
	Assorted	5x50 10x80 10x120	25	8	63642526710	3157625538405			
Machine Bran), BLACK & D AKITA, METAI		CH, DEWALT, ELU KIL	, FEIN, FESTO,			
Diameter (mm)	Grade	Grit	Quantity per Pack	Packs per Case	Article No.	Barcode			
	Fine	120	15	12	63642526715	3157625538436			
150	Medium	80	15	12	63642526713	3157625538429			
	Coarse	50	15	12	63642526712	3157625538412			
•••	Assorted	5x50 10x80 10x120	25	8	63642526714	3157625538443			
Machine Bran	d BOSCH, METABC	DEWALT, EI), PEUGEOT	LU, FELISATT , STAYER	I, FLEX, HITA	CHI, IBREX PRO T	OOL, KRESS,			



FIBRE DISCS

- High performance Aluminium Oxide for use on a variety of metal surfaces
- Extremely tough and durable fibre backing for longer life
- For use with the appropriate back-up pad (sold separately) **PREPACK**



PREFACK								
Diameter (mm)	Grade	Grit	Quantity per Pack	Packs per Case	Article No.	Barcode		
115	Fine	80	3	5	63642527535	3157625554535		
	Medium	50	3	5	63642527534	3157625554528		
	Coarse	36	3	5	63642527531	3157625554498		
			0		000.2027001	0.07020001.000		
Diameter (mm)	Grade	Grit	Quantity per Pack	Packs per Case	Article No.	Barcode		
	Grade Fine	Grit 80	Quantity					
(mm)			Quantity per Pack	per Case	Article No.	Barcode		

		100
1 martine		
AND B	3	11/a
Contraction of the second		K p
Neg.	119 E	190
	Y	A.

TRADE PACK										
Diameter (mm)	Grade	Grit	Quantity per Pack	Packs per Case	Article No.	Barcode				
115	Fine	80	10	10	63642527562	3157625554269				
	Medium	50	10	10	63642527561	3157625554252				
	Coarse	36	10	10	63642527550	3157625554245				
Diameter (mm)	Grade	Grit	Quantity per Pack	Packs per Case	Article No.	Barcode				
125	Fine	80	10	10	63642527565	3157625554603				
	Medium	50	10	10	63642527564	3157625554283				
	Coarse	36	10	10	63642527563	3157625554276				



125 x 22

BACKING PADS FOR FIBRE AND SEMI FLEXIBLE DISCS								
PREPACK								
Dimensions (mm) DxB	Quantity per Pack	Packs per Case	Article No.	Barcode				
115 x 22	1	5	63642556835	3157625568365				

5

63642556838

3157625568372

1



FLAP DISCS

a variety of surfaces

P

- · Ideal for sanding contoured metal surfaces
- · Angled flaps mean more abrasive makes contact with the workpiece than with a conventional fibre disc, increasing productivity
- Ideal for blending welds, deburring and finishing castings



Barcode
3157625554467
3157625554443
Barcode
3157625554481
3157625554474





PREPACK										
Diameter (mm)	Grade	Grit	Quantity per Pack	Packs per Case	Article No.	Barcode				
	Fine	120	10	10	63642526383	3157625530287				
125	Medium	80	10	10	63642526382	3157625530263				
	Coarse	50	10	10	63642526377	3157625530256				
•	Assorted	3x50 3x80 4x120	10	10	63642526496	3157625530898				



BACKING PAD FOR DRILL MOUNTABLE DISCS PREPACK							
Dimensions (mm) DxB	Quantity per Pack	Packs per Case	Article No.	Barcode			
125 x 12 x 6 (spindle)	1	5	63642556833	3157625568358			





MULTI SANDING SHEETS





DELTA SANDING SHEETS

QUICK RELEASE

PRFPACK

- High performance Aluminium Oxide for use on a variety of surfaces
- Hook and loop backing allows quick and easy sheet changing
- Fits most brands of delta sander



THEIACI	•					
Dimensions (mm) W	Grade	Grit	Quantity per Pack	Packs per Case	Article No.	Barcode
	Extra Fine	240	6	5	69957389834	8711479421648
94	Very Fine	180	6	5	69957389833	8711479421631
7 4	Fine	120	6	5	63642526401	3157625530416
	Medium	80	6	5	63642526400	3157625530409
•••	Coarse	50	6	5	63642526398	3157625530393
	Assorted	2x50 2x80 2x120	6	5	63642526505	3157625530966

Machine Brand BOSCH, MAKITA, METABO



TRADE PA	ACK					
Dimensions (mm) W	Grade	Grit	Quantity per Pack	Packs per Case	Article No.	Barcode
	Fine	120	15	12	63642526720	3157625538481
94	Medium	80	15	12	63642526719	3157625538474
	Coarse	50	15	12	63642526718	3157625538467
	Assorted	5x50 10x80 10x120	25	8	63642526721	3157625538498
Machine Brai	nd BOSC	H, MAKITA	, METABO			



DETAIL SANDING SHEETS QUICK RELEASE

- High performance Aluminium Oxide for use on a variety of surfaces
- · Hook and loop backing allows quick and easy sheet changing
- Available in 2 sizes that fit most brands of detail sander



PREPACK

Dimensions (mm) WxH	Grade	Grit	Quantity per Pack	Packs per Case	Article No.	Barcode
	Extra Fine	240	6	5	69957389810	8711479421396
95x145	Very Fine	180	6	5	69957389812	8711479421419
JJX17J	Fine	120	6	5	63642526409	3157625530485
	Medium	80	6	5	63642526408	3157625530478
	Coarse	50	6	5	63642526407	3157625530461
	Assorted	2x50 2x80 2x120	6	5	63642526508	3157625530997
Machine Brai	nd BLACK 8	DECKER				
Dimensions (mm) WxH	Grade	Grit	Quantity per Pack	Packs per Case	Article No.	Barcode
102x152	Extra Fine	240	6	5	63642596427	3157625717725
	Very Fine	180	6	5	63642596421	3157625717718
	Fine	120	6	5	63642596419	3157625717701
	Medium	80	6	5	63642596418	3157625717695
	Coarse	50	6	5	63642596395	3157625717688
Machine Bra	nd BOSCH,	METABO				
Dimensions (mm) WxH	Grade	Grit	Quantity per Pack	Packs per Case	Article No.	Barcode
	Extra Fine	240	6	5	69957389809	8711479421389
105x175	Very Fine	180	6	5	69957389808	8711479421372
	Fine	120	6	5	63642526405	3157625530454
	Medium	80	6	5	63642526404	3157625530447
	Coarse	50	6	5	63642526402	3157625530423
	Assorted	2x50 2x80 2x120	6	5	63642526506	3157625530973
Machine Brai	nd BLACK 8	DECKER				



TRADE PA	ICK					
Dimensions (mm) WxH	Grade	Grit	Quantity per Pack	Packs per Case	Article No.	Barcode
105x175	Fine	120	15	12	63642526728	3157625538528
	Medium	80	15	12	63642526726	3157625538511
	Coarse	50	15	12	63642526722	3157625538504
	Assorted	5x50 10x80 10x120	25	8	63642526729	3157625538535
Machine Bran	d BLACK 8	DECKER				



SANDING BELTS



CLOTH SANDING BELTS

- High performance Aluminium Oxide for use on a variety of surfaces
- Tough and durable cloth backing for increased durability and longer product life
- · Available in multiple sizes to fit most brands of belt sander



PREPACK									
Dimensions (mm) WxL	Grade	Grit	Quantity per Pack	Packs per Case	Article No.	Barcode			
60x400	Fine	120	2	5	69957389986	8711479423321			
60x400	Medium	80	2	5	69957389985	8711479423314			
60x400	Coarse	50	2	5	69957389976	8711479423321			
Machine Brand BLACK & DECKER, MAKITA, METABO, PEUGEOT, SKIL, STAYER, WEN									
Dimonsions	Grada	Cuit	Quantity	Dacks	Article No	Parcada			

Dimensions (mm) WxL	Grade	Grit	Quantity per Pack	Packs per Case	Article No.	Barcode
65x410	Fine	120	2	5	69957390000	8711479424977
65x410	Medium	80	2	5	69957389998	8711479423468
65x410	Coarse	50	2	5	69957389997	8711479423451
Machine Bran	d BLACK		FR. MAKITA.	METABO, PE	UGEOT, SKIL, STAY	YFR. WFN

Dimensions (mm) WxL	Grade	Grit	Quantity per Pack	Packs per Case	Article No.	Barcode
75x457	Fine	120	2	5	63642526464	3157625530737
75x457	Medium	80	2	5	63642526463	3157625530713
75x457	Coarse	50	2	5	63642526461	3157625530706

Machine Brand BLACK & DECKER, MAKITA, METABO, PEUGEOT, SKIL, STAYER, WEN

Dimensions (mm) WxL	Grade	Grit	Quantity per Pack	Packs per Case	Article No.	Barcode
75x533	Fine	120	2	5	63642526470	3157625530768
75x533	Medium	80	2	5	63642526469	3157625530751
75x533	Coarse	50	2	5	63642526466	3157625530744

Machine Brand AEG/ATLAS COPCO, BLACK & DECKER, BOSCH, CASALS, DEWALT, FREUD, HITACHI, HOLZ HER, MAKITA, METABO, PEUGEOT, PORTER CABLE, RHINO, ROCKWELL, RYOBI, SKIL, STANLEY

46

10x(

PREPACK						
Dimensions (mm) WxL	Grade	Grit	Quantity per Pack	Packs per Case	Article No.	Barcode
100x560	Fine	120	2	5	63642526476	3157625530799
100x560	Medium	80	2	5	63642526474	3157625530782
100x560	Coarse	50	2	5	63642526471	3157625530775
Machine Brai			,	ECKER, DEW	ALT, ELU, FESTO,	FESTOOL,
	HAFFNE	R, RYOBI,	SKIL			
Dimensions (mm) WxL	Grade	Grit	Quantity per Pack	Packs per Case	Article No.	Barcode
	-	,,	Quantity		Article No. 63642526479	Barcode 3157625530829
(mm) WxL	Grade	Grit	Quantity per Pack	per Case		
(mm) WxL 100x610	Grade Fine	Grit 120	Quantity per Pack 2	per Case 5	63642526479	3157625530829

METABO, PORTER CABLE, ROCKWELL, RYOBI, STANLEY, WOLF



TRADE PA	СК						
Dimensions (mm) WxL	Grade	Grit	Quantity per Pack	Packs per Case	Article No.	Barcode	
60x400	Fine	120	4	7	63642526737	3157625538627	
60x400	Medium	80	4	7	63642526736	3157625538603	
60x400	Coarse	50	4	7	63642526735	3157625538597	
60x400	Assorted	2x50 2x80 2x120	6	7	63642526739	3157625538634	
Machine Bran	d BLACK &	& DECKER,	MAKITA, ME	TABO, PEUC	GEOT, SKIL, STAY	ER, WEN	
Dimensions (mm) WxL	Grade	Grit	Quantity per Pack	Packs per Case	Article No.	Barcode	
65x410	Fine	120	4	7	63642526742	3157625538665	
65x410	Medium	80	4	7	63642526741	3157625538658	
65x410	Coarse	50	4	7	63642526740	3157625538641	
65x410	Assorted	2x50 2x80 2x120	6	7	63642526746	3157625538672	
Machine Bran	d BLACK &	& DECKER,	MAKITA, MET	rabo, peugi	EOT, SKIL, STAYEF	R, WEN	
Dimensions (mm) WxL	Grade	Grit	Quantity per Pack	Packs per Case	Article No.	Barcode	
75x457	Fine	120	4	7	63642526783	3157625538702	
75x457	Medium	80	4	7	63642526782	3157625538696	
75x457	Coarse	50	4	7	63642526777	3157625538689	
75x457	Assorted	2x50 2x80 2x120	6	7	63642526784	3157625538719	
Machine Bran	d BLACK &	& DECKER,	MAKITA, MET	TABO, PEUGI	EOT, SKIL, STAYEF	R, WEN	
Dimensions (mm) WxL	Grade	Grit	Quantity per Pack	Packs per Case	Article N & arco	ode	
75x510	Assorted	2x50 2x80 2x120	4	7	69957390006	8711479423543	
2x80							





TRADE PACK

Dimensions (mm) WxL	Grade	Grit	Quantity per Pack	Packs per Case	Article No.	Barcode
75x533	Fine	120	4	7	63642526788	3157625538757
75x533	Medium	80	4	7	63642526787	3157625538733
75x533	Coarse	50	4	7	63642526785	3157625538726
75x533	Assorted	2x50 2x80 2x120	6	7	63642526790	3157625538764

Machine Brand AEG/ATLAS COPCO, BLACK & DECKER, BOSCH, CASALS, DEWALT, FREUD, HITACHI, HOLZ HER, MAKITA, METABO, PEUGEOT, PORTER CABLE, RHINO, ROCKWELL, RYOBI, SKIL, STANLEY

		,	/- /-			
Dimensions (mm) WxL	Grade	Grit	Quantity per Pack	Packs per Case	Article No.	Barcode
100x552	Fine	120	4	7	63642526803	3157625538795
100x552	Medium	80	4	7	63642526802	3157625538788
100x552	Coarse	50	4	7	63642526796	3157625538771
100x552	Assorted	2x50 2x80 2x120	6	7	63642526805	3157625538801

Machine Brand AEG/ATLAS COPCO, BLACK & DECKER, DEWALT, ELU, FESTO, FESTOOL, HAFFNER, RYOBI, SKIL

Dimensions (mm) WxL	Grade	Grit	Quantity per Pack	Packs per Case	Article No.	Barcode
100x560	Fine	120	4	7	63642526809	3157625538832
100x560	Medium	80	4	7	63642526808	3157625538825
100x560	Coarse	50	4	7	63642526807	3157625538818
100x560	Assorted	2x50 2x80 2x120	6	7	63642526810	3157625538849

Machine Brand AEG/ATLAS COPCO, BLACK & DECKER, DEWALT, ELU, FESTO, FESTOOL, HAFFNER, RYOBI, SKIL

Dimensions (mm) WxL	Grade	Grit	Quantity per Pack	Packs per Case	Article No.	Barcode
100x610	Fine	120	4	7	63642526815	3157625538887
100x610	Medium	80	4	7	63642526813	3157625538863
100x610	Coarse	50	4	7	63642526812	3157625538856
100x610	Assorted	2x50 2x80 2x120	6	7	63642526816	3157625538894
Machine Brai	nd AEG/AT	LAS COPCO	O, BOSCH, HI	TACHI, KANG	GO, KNOPP, LYON	FLEX, MAKITA,

METABO, PORTER CABLE, ROCKWELL, RYOBI, STANLEY, WOLF



CLOTH POWER FILE SANDING BELTS

- High performance Aluminium Oxide for use on a variety of surfaces
- Tough and durable cloth backing for increased durability and longer product life





PREPACK								
Dimensions (mm) WxL	Grade	Grit	Quantity per Pack	Packs per Case	Article No.	Barcode		
13x454	Fine	120	4	10	63642526460	3157625530683		
13x454	Medium	80	4	10	63642526439	3157625530676		
13x454	Coarse	50	4	10	63642526438	3157625530669		
13x454	Extra Coarse	36	4	10	63642526437	3157625530652		
Machine Brai	nd BLACK & D	ECKER						
Dimensions (mm) WxL	Grade	Grit	Quantity per Pack	Packs per Case	Article No.	Barcode		
40x303	Fine	120	3	5	63642526435	3157625530645		
40x303	Medium	80	3	5	63642526433	3157625530638		
40x303	Coarse	50	3	5	63642526431	3157625530621		
Machine Brai	nd BOSCH							



TRADE PACK								
Dimensions (mm) WxL	Grade	Grit	Quantity per Pack	Packs per Case	Article No.	Barcode		
13x454	Fine	120	6	20	63642526732	3157625538566		
13x454	Medium	80	6	20	63642526731	3157625538559		
13x454	Coarse	50	6	20	63642526730	3157625538542		
13x454	Assorted	2x50 2x80 2x120	6	20	63642526733	3157625538573		
Machine Bra	nd BLACK & D	DECKER						

Dimensions (mm) WxL	Grade	Grit	Quantity per Pack		Article No.	Barcode
40x303	Assorted	2x50 2x80 2x120	6	7	69957390005	8711479423536

Machine Brand BOSCH



SANDING BLOCK KITS & SPONGES



SANDING SPONGES – STANDARD

DUAL GRIT

- Ideal for sanding flat and contoured surfaces
- Two grits per sponge for maximum durability
- Can be washed and reused



PREPACK								
	Dimensions (mm) HxWxT	Grade	Quantity per Pack	Packs per Case	Article No.	Barcode		
	100x68.5x26	Fine/Medium	1	20	63642556852	3157625568419		
	100x68.5x26	Medium/Coarse	1	20	63642556853	3157625568426		



	SANDING SPONGES – LARGE								
I.	DUAL GRIT								
	 Ideal for sanding flat and contoured surfaces Two grits per sponge for maximum durability Can be washed and reused 								
	PREPACK								
	Dimensions (mm) HxWxT	Grade	Quantity per Pack	Packs per Case	Article No.	Barcode			

8

63642556850

DOUBLE ANGLED SPONGES

Fine/Medium



3157625568402

• Specially designed for sanding into angles, contours, and corners

1

- Two grits per sponge for maximum durability
- Can be washed and reused

225x76x25

DUAL GRIT

PREPACK	PACK							
Dimensions (mm) HxWxT	Grade	Quantity per Pack	Packs per Case	Article No.	Barcode			
126x72x26	Fine/Medium	1	10	63642556855	3157625568433			
126x72x26	Medium/Coarse	1	10	63642556856	3157625568457			

LIGHTWEIGHT SANDING BLOCK KIT

 General purpose aluminium oxide abrasive for maximum durability · Lightweight block for sanding flat surfaces

PREPACK						
Dimensions (mm) WxH	Grade	Grit	Quantity per Pack	Packs per Case	Article No.	Barcode
70x230	Assorted	1x50 2x80 2x120	1 block + 5 sheets	5	63642556827	3157625568334

QUICK RELEASE SANDING BLOCK KITS



- · Hook and loop backing allows quick and easy sheet changing
- · Foam block for comfortable sanding

maximum durability

Grade

Fine

Medium

Coarse

PREPACK Dimensions

(mm) WxH

70x125

70x125

70x125

· General purpose aluminium oxide abrasive for maximum durability



PREPACK							
Dimensions (mm) WxH	Grade	Grit	Quantity per Pack	Packs per Case	Article No.	Barcode	
70x125	Assorted	1x50 1x80 1x120	1 block + 3 sheets	5	63642556830	3157625568341	



TRADE P/	TRADE PACK								
Dimensions (mm) WxH	Grade	Grit	Quantity per Pack	Packs per Case	Article No.	Barcode			
70x125	Assorted	5x50 5x80 5x120	1 block+ 15 sheets	10	63642557513	3157625569508			

QUICK RELEASE SANDING BLOCK KIT REFILL

Grit

120

80

50




Barcode

3157625530249

3157625530232

3157625530225



Article No.

63642526349

63642526348

63642526346



TRADE PA	ICK						
Dimensions (mm) WxH	Grade	Grit	Quantity per Pack	Packs per Case	Article No.	Barcode	
70x125	Fine	120	15	12	63642526700	3157625538306	
70x125	Medium	80	15	12	63642526699	3157625538283	
70x125	Coarse	50	15	12	63642526698	3157625538276	
70x125	Assorted	5x50 10x80 10x120	25	8	63642526701	3157625538313	

Quantity

per Pack

6

6

6









DIAMOND BLADES

- 54 Useful Information
- 56 Building Materials General Purpose
- 57 Concrete and Reinforced Concrete
- 58 Ceramic and Stone Tiles
- 59 Roof Tiles, Granite and Hard Materials




USEFUL INFORMATION

The use of Diamond Blades within the merchandising environment is rapidly growing as enthusiasts and professionals become increasingly more knowledgeable and experienced, demanding better finishes and faster results. With an in-depth knowledge of the construction and building industry Flexovit provides a range of Diamond Blades to meet any demand.

All Flexovit Diamond Blades conform to the highest European safety standard, EN13236, which ensures that all products are manufactured and tested to the highest quality. All Flexovit products are laser-marked in accordance with the requirements of EN13236.

UNDERSTANDING THE PRODUCT



DIFFERENTIATION WITHIN THE RANGE

Where greater differentiation is needed within a range, this is done through colour coding and application instructions.



Building Materials

Concrete & Reinforced Concrete Ceramic & Stone Tiles

Roof Tiles, Granite & Hard Materials

SELECTING THE RIGHT PRODUCT

The Flexovit product line contains a wide range of diamond blades suitable for many different applications, in sizes ranging from 100mm to 230mm diameter, for use with portable angle grinders and small tile saws.

When choosing a diamond blade it is important to carefully consider the material to be cut as using the blade for its specific purpose prolongs the life and cutting speed.

Flexovit PRO diamond blades have premium attributes that give more advanced and professional performance levels. With Flexovit PRO Precision Cutting Diamond Blades there is significantly less chance of any chipping, burrs, or burn. The increased accuracy and thinner blades means they are much easier to use. Also less heat and dust is generated as a lower proportion of the wheel is in direct contact with the workpiece – resulting in a much cleaner, precise cut.

If the blade is used frequently then a Flexovit PRO with laser welded 10mm high segments should be used.

To aid product selection the application materials have been classified into four main areas, each with a unique colour coding.



Building Materials – General Purpose

For use on most types of building materials, including building bricks, breeze blocks, paving slabs, concrete curb stones and clay roof tiles. The products have a segmented design where the diamond segments are sintered (baked) on to the steel core. Typically the blades have 7mm high segments and last more than 50 times longer than conventional cutting-off wheels. However, the Flexovit PRO (longer life) segmented diamond blade features 10mm high segments and lasts more than 40% longer than the standard blades.



Concrete and Reinforced Concrete

Concrete and reinforced concrete blades are manufactured by fusing the pre-sintered diamond segments to the metal centre of the blade using a laser. This gives increased strength compared to sintered blades and increases the strength of the bond between the diamond segments and the steel core. This makes the blades ideal for intensive use on hard compact materials that are difficult to cut, such as concrete, reinforced concrete, clay roof tiles, and hard building bricks.

Standard blades have 7mm high segments and last more than 75 times longer than cutting-off wheels. However, the PRO (longer life) segmented diamond blade featuring 10mm high segments generally last 40% longer than the standard blades.



Ceramic and Stone Tiles

These diamond blades have been specifically designed for cutting ceramic and stone tiles. When working with these materials the quality of cut is extremely important and a continuous rim diamond blade is most effective. The continuous rim is designed to achieve a smooth, fine edge.

For a very precise and accurate cut Flexovit PRO (precision) with its ultra thin 1.4mm thickness, should be used. It gives excellent quality, a very accurate cut and minimized chance of chipping the work piece. Continuous rim blades can be used wet or dry, but using wet is advised to achieve the ultimate cut.



Roof Tiles, Granite and Hard Materials

Hard materials, such as roof tiles, granite, and marble, are most effectively cut using a Continuous Rim Turbo diamond blade. Its turbo rim makes the product much smoother and easier to use than segmented blades. The standard rim height is 7mm, but the PRO (longer life) blade features 10mm high segments and lasts more than 40% longer than the standard blades.



BUILDING MATERIALS – GENERAL PURPOSE






SEGMENTED SINTERED

• 10mm high segments give longer cutting life

• For cutting general purpose building materials






•	Dimensions (mm) DxHxTxB	Product Name	Quantity per Pack	Article No.	Barcode
	115x10x2x22.23	SR 115 PRO	1	70184622072	5450248232100
	125x10x2.1x22.23	SR 125 PRO	1	70184622073	5450248232117
	230x10x2.5x22.23	SR 230 PRO	1	70184622074	5450248232124
80	300x10x2.5x20	SR 300 PRO	1	70184623843	5450248234913

SEGMENTED SINTERED

- Economy product
- For cutting general purpose building materials





	Dimensions (mm) DxHxTxB	Product Name	Quantity per Pack	Article No.	Barcode
	115x7x2x22.23	SR 115	1	70184622068	5450248232063
	125x7x2.1x22.23	SR 125	1	70184622069	5450248232070
	180x7x2.4x22.23	SR 180	1	70184622070	5450248232087
30 im	230x7x2.5x22.23	SR 230	1	70184622071	5450248232094

SEGMENTED BRAZED MORTAR RAKER

- Especially designed for renovating brick walls
- Extra thick diamond blade for removing
- mortar joints



	mortarjonits				
125	Dimensions (mm) DxHxTxB	Product Name	Quantity per Pack	Article No.	Barcode
	115x7x6.5x22.23 – Extra Thick 6.5mm	TP 115	1	70184622066	5450248232049
1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	125x7x6.5x22.23 – Extra Thick 6.5mm	TP 125	1	70184622067	5450248232056

CONCRETE & REINFORCED CONCRETE







SEGMENTED LASER WELDED

- 10mm high segments give longer cutting life
- · Segments are laser welded for enhanced performance
- Enhanced specification for a smooth cut
- For cutting concrete, reinforced concrete and general purpose building materials

Dimensions (mm) DxHxTxB	Product Range	Quantity per Pack	Article No.	Barcode
230x10x2.5x22.23	SR 230 LASER PRO	1	70184622065	5450248232032

SEGMENT	ED LASER	WELDED		K		2
general purpo	ncrete, reinforced se building mate laser welded for o	rials	mance	YP I		
Dimonsions	Droduct	Quantity	Anticla	Ne	Parcodo	



	-					
	Dimensions (mm) DxHxTxB	Product Range	Quantity per Pack	Article No.	Barcode	
l	115x7x2.2x22.23	SR 115 LASER	1	70184622062	5450248232001	
L	125x7x2.2x22.23	SR 125 LASER	1	70184622063	5450248232018	
L	230x7x2.5x22.23	SR 230 LASER	1	70184622064	5450248232025	
	300x7x2.5x20	SR 300 LASER	1	70184623842	5450248234906	

DOUBLE RIMMED CUP GRINDER

- Universal grinding cup designed for surface treatment
- For levelling concrete, reinforced concrete and general purpose building materials

Dimensions (mm) DxHxTxB	Product Range	Quantity per Pack	Article No.	Barcode
100x5x8x22.23/16	MR 100	1	70184622076	5450248232131
125x5x8x22.23	MR 125	1	70184622077	5450248232148








CERAMIC & STONE TILES





CORRUGATED RIM THIN CUT SINTERED

- Ultra thin blade gives an excellent quality, highly accurate cut (no chipping)
- Designed for cutting ceramic and stone tiles
- Jet rim for improved blade performance





	Name	perrack		
.4x22.23 - n 1.4mm	CR 115 PRO	1	70184622054	5450248231936
.4x22.23 - n 1.4mm	CR 125 PRO	1	70184622055	5450248231943

CONTINUOUS RIM SINTERED

- Designed for cutting ceramic and stone tiles
- Continuous rim gives a good quality cut
- 180x25.4/22.23 can work on both bench tile saws and angle grinders

58

	Dimensions (mm) DxHxTxB	Product Name	Quantity per Pack	Article No.	Barcode
	115x5x1.8x22.23	CR 115	1	70184622050	5450248231899
	125x5x1.8x22.23	CR 125	1	70184622051	5450248231905
P	180x5x1.8x25.4/22.23	CR 180	1	70184622053	5450248231929
25 1m	230x5x1.8x22.23	CR 230	1	70184622052	5450248231912



ROOF TILES, GRANITE & HARD MATERIALS







Dimensions (mm) DxHxTxB	Product Name	Quantity per Pack	Article No.	Barcode
115x10x2.1x22.23	CR 115 TURBO PRO	1	70184622059	5450248231981
230x10x2.6x22.23	CR 230 TURBO PRO	1	70184622060	5450248231998



- For cutting hard materials
- Turbo rim for a smooth high quality cut





Dimensions (mm) DxHxTxB	Product Name	Quantity per Pack	Article No.	Barcode
115x7x2.1x22.23	CR 115 TURBO	1	70184622056	5450248231950
125x7x2.1x22.23	CR 125 TURBO	1	70184622057	5450248231967
230x7x2.6x22.23	CR 230 TURBO	1	70184622058	5450248231974









ACCESSORIES

- 62 Useful Information
- 64 Steel Wire Wheels and Brushes
- 66 Buffing and Polishing Products
- 67 Fibreflex Discs
- 68 Backing Pads and Adaptor Shafts



USEFUL INFORMATION

In addition to the core abrasives range, Flexovit offers a number of accessories which compliment the range providing a complete abrasives solution.

Within accessories Flexovit provides polishing products, and steel wire brushes, as well as a range of back-up pads for use with coated abrasive discs.

STEEL WIRE BRUSHES

Flexovit offers a comprehensive range of steel wire brushes for use with electric drills, angle grinders, bench grinders, and pedestal grinders. All of the products are designed for cleaning and general surface preparation of wood, paint or metal but the different types give each product specific qualities making them more suitable for different applications.

Selecting the Right Product

All Steel Wire Brushes can be used on wood, metal or painted surfaces.



General Cleaning

Steel Wire Brush

This product is used for general cleaning, light rust removal and deburring metal. It can also be used on wood and paint. Being drill mounted makes this product extremely flexible.



Steel Wire Cup Brush

Designed for general cleaning of wood, paint, and metal, this product can be used with most types of electric drill.



Steel Wire End Brush

The steel wire end brush is designed for general cleaning, rust removal and deburring of hard to reach areas and intricate contours. It can be used on most electric drills which makes this product very flexible.



Light/Medium Cleaning

Crimped Steel Wire Cup Brush

This multipurpose product is designed for use on angle grinders. Crimped wire is very flexible and therefore ideally suited to light rust removal and surface treatment, as well as removing light burrs.



Crimped Steel Wire Wheel

This multipurpose product is designed for use on bench grinders. Reduction rings are included in the pack allowing the bore size to be reduced from the standard dimension to fit most types of machine. Crimped wire is extremely flexible and therefore ideally suited to light rust removal and surface treatment, as well as removing light burrs.



Heavy Cleaning

Twisted knot steel wire cup brush

This product is ideal for rust removal, cleaning welds, and extreme cleaning of large areas. The twisted wire is generally less flexible than crimped wire. For use on angle grinders.

BUFFING AND POLISHING PRODUCTS

The range of buffing and polishing products offered by Flexovit is designed to encompass and surpass all consumer requirements encountered within a merchandising environment. The range includes products for use on electric drills, orbital sanders, angle grinders, and bench grinders. All of the products are designed for use on either plastic or metal surfaces. Compound blocks are also available adding to the products' performance in providing the ultimate surface finish.

Selecting the Right Product



Buffing Wheel

Designed for use on bench and pedestal grinders, buffing wheels are ideal for polishing, finishing or removing dust from metal or PVC surfaces. They can be used with or without a polishing compound and are available in 2 different sizes.

This product is manufactured from wool making it ideal for polishing, finishing, or waxing metal or PVC surfaces. It can be used on an eccentric sander, electric drill, or angle grinder (max 35 m/s). It has a hook and loop backing that allows quick and easy disc changing and can be used with or without a polishing compound.



Polishing Sponge

This sponge can be used for polishing, finishing, or waxing metal or PVC surfaces. It can be used on an eccentric sander, electric drill, or angle grinder (max 35 m/s). It has a hook and loop backing that allows quick and easy disc changing and can be used with or without a polishing compound.



Polishing Blocks

Green Block

Used to accompany a polishing wheel or disc, in order to produce a high gloss finish on metal and PVC surfaces.

Brown Block

Used to accompany a polishing wheel or disc, to clean dirt from metal or PVC surfaces.





STEEL WIRE WHEELS & BRUSHES



STEEL WIRE BRUSHES

• For general cleaning of wood, paint and metal

- 6mm spindle, for use with most electric drills
- Suitable for light rust removal and deburring




· Suitable for light rust removal and deburning							
	Diameter (mm)	Grade	Max RPM/ M/S	Quantity per Pack	Packs per Case	Article No.	Barcode
	75x6 (spindle)	Coarse	4500	1	10	63642556882	3157625568556
	100x6 (spindle)	Coarse	4500	1	10	63642556883	3157625568563

STEEL WIRE END BRUSH

• For general cleaning of wood, paint and metal

- 6mm spindle, for use with most electric drills
- Suitable for light rust removal and deburring









Diameter (mm)	Grade	Max RPM/ M/S	Quantity per Pack	Packs per Case	Article No.	Barcode
50 x 6 (spindle)	Coarse	4500	1	10	63642556885	3157625568587
75 x 6 (spindle)	Coarse	4500	1	10	63642556887	3157625568594



For light/medium cleaning of wood, paint and metal Ideal for light rust removal, surface treatment and removing burrs For use with angle grinders Diameter Grade Max RPM/ Quantity Packs Article No. Bar

Diameter (mm)	Grade		Quantity per Pack		Article No.	Barcode
60	Medium	12500	1	3	63642556881	3157625568549

	CRIMF	PED S	TEEL V	VIRE	WHEELS	5
--	-------	-------	--------	------	--------	---

STEEL WIRE CUP BRUSHES • For general cleaning of wood, paint and metal • 6mm spindle, for use with most electric drills

• For light/medium cleaning of wood, paint and metal

CRIMPED STEEL WIRE CUP BRUSH

- For use with Bench grinders
- Ideal for light rust removal, surface treatment and removing burrs
- Reduction rings included





0



- For Heavy Cleaning of wood, paint and metal
 For use with angle grinders
- · Ideal for rust removal, cleaning welds and extreme cleaning of large areas

Diameter (mm)	Grade	Max RPM/ M/S	Quantity per Pack		Article No.	Barcode
65	Coarse	12500	1	3	63642556880	3157625568532





BUFFING & POLISHING PRODUCTS







• For use on a bench or pedestal grinder								
Diameter (mm)	Max RPM/ M/S	Quantity per Pack		Article No.	Barcode			
125	35	1	5	63642556858	3157625568464			
150	35	1	5	63642556860	3157625568471			

FLEECE BONNET

BUFFING WHEELS

metal or PVC surfaces

• For polishing, finishing and removing dust from

- For polishing, finishing or waxing metal or PVC surfaces
- Hook and loop quick change backing
- Can be used with or without a polishing compound · Can be used on an angle grinder, eccentric sander,
- or electric drill



Diameter (mm)	Quantity per Pack	Packs per Case	Article No.	Barcode
125	1	5	63642556861	3157625568488

	 For polishing, fi Hook and loop Can be used with 	G SPONGE inishing or waxing ma quick change backin ith or without a polish n an angle grinder, ec	ig hing compound		
	Diameter (mm)	Quantity per Pack	Packs per Case	Article No.	Barcode
	125	1	5	63642556862	3157625568495



flexovit

POLISHING COMPOUND BLOCKS									
• For use with a buffing wheel, fleece bonnet or polishing sponge									
Colour	Application	Quantity per Pack	Packs per Case	Article No.	Barcode				
Brown Polishing Compound Block	Cleaning Dirt	1	5	63642556865	31576255				
Green Polishing Compound Block	Providing a high gloss finish	1	5	63642556863	31576255				

FIBREFLEX DISCS



FIBREFLEX DISCS

• Semi-flexible discs for rough surface grinding of brick, stone, concrete and other building materials





	PREPACK					
l	Diameter (mm)	Grit	Quantity per Pack	Packs per Case	Article No.	Barcode
	127	36	1	5	63642556839	3157625568389
	180	36	1	5	63642556840	3157625568396





BACKING PADS & ADAPTOR SHAFTS



BACKING PADS FOR FIBRE & SEMI FLEXIBLE DISCS

BACKING PAD FOR DRILL MOUNTABLE DISCS



• For use with all angle grinders • For fibre discs and all types of semi-flexible discs

l	Dimensions (mm) DxB	Quantity per Pack	Packs per Case	Article No.	Barcode
L	115 x 22	1	5	63642556835	3157625568365
-	125 x 22	1	5	63642556838	3157625568372



• 6mm spindle, for use most electric drills	with			
Dimensions (mm) DxB	Quantity per Pack	Packs per Case	Article No.	Barcode
125 x 12 x 6 (spindle)	1	5	63642556833	3157625568358









TECHNICAL INFORMATION

- 70 Cutting-Off and Grinding Wheels
- 73 Bonded Abrasives
- 77 Coated Abrasives
- 79 Diamond Blades



TECHNICAL INFORMATION

CUTTING-OFF AND GRINDING WHEELS



General Safety

Instructions for use

Cutting-Off and Grinding wheels should only be used on materials for which they are suitable. This is shown by means of pictograms on the product, the packaging and in the catalogue.

Cutting-Off Wheels

When using cutting-off wheels, keep the wheel straight in the cut and apply light pressure – let the wheel do the work.

Grinding Wheels

When using grinding wheels keep the wheel at an angle of 30-40 degrees to the work piece.

Safety Measures

Suitable eye protection must be worn. It is recommended that other safety equipment is also used.





Damaged Wheel

Protection of the Workpiece

Portable Angle grinders should be used in such a manner that sparks fly away from the operator's body and any flammable material.

Safety Guards

The wheel guard of the machine must be in position and securely fixed.

Stopping the Machine

Switch off the machine and allow the wheel to stop completely before placing it on a bench or on the floor. Never bring the wheel to rest by applying pressure to the wheel surface.

Shelf Life of Cutting-Off and Grinding Wheels

All cutting-off and grinding wheels have a use by date engraved on the metal bore ring. Wheels should not be used after this date.

Troubleshooting Guide

To get the best from Flexovit cutting-off and grinding wheels it is important that you:

- Determine the material application and select the most suitable Flexovit wheel. Using the right wheel for the right material is very important for the life and cutting/grinding behaviour of the wheel. Please consult your local Customer Service or Sales Representative, if in doubt.
- Check the machine is operating correctly and that the machine does not exceed the speed indicated on the wheel. Always use the wheel at its recommended speed.

Below is a troubleshooting guide that will help you recognise and solve some of the most common problems associated with cutting-off and grinding.

CUTTING-OFF WHEELS: Type 41 Type 42			
Problem	Possible cause	Solution	
Excessive wheel wear	In case of white cutting edge: Wheel too soft Operating speed too low Decrease of rpm during cutting	Use harder wheel Increase rpm up to max. (80m/sec) Use machine with more power Reduce pressure on the machine	
Wheel does not cut	In case of blue cutting: Wheel too hard or too thick Peripheral speed too low	Use softer or thinner Flexovit wheels Check peripheral speed Increase rpm up to max. (80m/sec)	
Crumbled wheel edge	Cutting-Off wheel used for grinding operations Work piece is moving Too much side-pressure	Use a grinding wheel for grinding operations Clamp the work piece properly Add only the radial pressure to the wheel	
Arborhole or centre break out	Wheel sticks in the work piece / material Cutting-Off wheel used for grinding operations Too much side pressure Different diameter top/bottom flange	Use more radial pressure and swing the wheel forwards and backwards Use a grinding wheel for grinding operations Add only the radial pressure to the wheel Use flanges with the same diameter	

GRINDING WHEELS:		Type 27
Problem	Possible cause	Solution
Excessive wheel wear	Wheel too soft Too much pressure Decrease of peripheral speed Too low peripheral speed	Use harder wheel Reduce pressure, let the wheel do the grinding Use machine with more power Reduce pressure on the machine Max. 80 m/s is optimum speed
Wheel does not grind	Wheel too hard, wheel glazing Not enough pressure Machine power too low	Use softer wheel Increase pressure Use machine with more power
Crumbled wheel edge	Grinding angle too flat Work piece is moving Too much pressure	Change angle to 30–40° Clamp the work piece properly Reduce pressure, let the wheel do the grinding
Out of Balance (vibration)	Dirty flanges Wheel mounting insecure Flanges with different diameter	Clean flanges Tighten flanges Replace flanges



SAFETY ADVICE – DO'S AND DON'TS:

For your safety you should ensure that you are fully aware of how to safely use cutting-off and grinding wheels.

- **DO** always handle and store wheels carefully. All cutting and grinding wheels should be placed on top of each other or stored in the original packaging.
- **DO** always visually inspect all wheels before mounting for possible damage in transit.
- **DO** always use a safety guard and ensure that it is correctly positioned and securely fitted. It should cover at least one half of the wheel and protect the operator in the unlikely event of a wheel breakage.
- **DO** always switch 'OFF' the power at supply source and/or remove the plug from the socket before changing the wheel.
- **DO** always use the tools supplied by the machine manufacturer to change the wheel.
- **DO** always ensure that the speed of the machine does not exceed the operating speed marked on the wheel.
- **DO** allow newly mounted wheels to run at operating speed, with the guard in place, for a reasonable time before cutting or grinding.
- **DO** always wear EYE PROTECTION.
- **DO** always wear appropriate safety clothing such as DUST MASK, GLOVES, EAR PROTECTION, OVERALLS AND SAFETY SHOES.
- **DO** always secure the workpiece firmly while it is being cut or ground.
- **DO** grind at an angle above 30 degrees to the workpiece with a depressed centre grinding wheel.
- **DO** keep the working area around cutting and grinding operations clear.

DON'TS!

XXXXXXXXXXXX

- **DON'T** store wheels in a damp atmosphere or in extreme temperatures.
- **DON'T** mount a damaged wheel.
- **DON'T** EVER exceed the maximum operating speed marked on the wheel.
- **DON'T** force a wheel onto a machine spindle.
- **DON'T** tighten the mounting nut or locking flange excessively. Doing so can distort the flanges.
- **DON'T** use a machine which is not in good mechanical condition.
- **DON'T** use a machine without a wheel guard.
- **DON'T** use wheels without proper ventilation or dust protection equipment.
- **DON'T** stop the wheel by applying pressure to the periphery or face. Always switch the machine off and allow the wheel to stop revolving.
- **DON'T** allow the wheel to be trapped or pinched in the cut.
- **DON'T** apply excessive pressure onto the wheel so that the driving motor slows down.
- **DON'T** grind on the side of cutting-off wheels.
- **DON'T** grind with a depressed centre grinding wheel at an angle below 30 degrees to the workpiece.





Safety in the Use and Storage of Grinding Wheels

Stringent safety standards are maintained throughout the manufacture of Flexovit Bonded abrasives. To further reduce the risk of accidents, the law requires that certain basic precautions are taken in the storage and use of abrasive wheels.

The following points are intended to act as a reminder for those involved in the storage and use of grinding wheels. It is no substitute for careful study of the full regulations and codes of practice. Anyone requiring advice on specific safety matters relating to grinding wheels should contact their local Customer Service Centre detailed on the back cover of this catalogue.

Further information on bonded safety, together with advice on operating speeds and machine types can be found in safety booklets issued by FEPA (Federation of European Producers of Abrasives).

Personal Protection

Safety goggles, ear muffs, safety gloves, dust masks, leather aprons and safety shoes must be worn.

Storage

Always store and handle bonded abrasive products carefully. Storage conditions should be dry and free from large temperature variations.

Testing the Product prior to use - The Ring Test

Always examine a product for damage before mounting. The best method of inspecting a vitrified grinding wheel is by performing a ring test.

The ring test must be performed before the wheel is mounted on a grinding machine. Ring tests depend on the dampening characteristics of a cracked wheel altering the sound emitted when the wheel is tapped lightly. To perform the ring test wheels should be held through the bore at a 45 degree angle to the ground and then tapped gently on both sides with a light non-metallic element, such as the handle of a screwdriver.

An undamaged wheel will give a clear tone. If cracked, there will be a dead sound and not a clear ring. In this instance the wheel should not be used.

Wheels must be dry and free from packaging when doing the ring test.

Wheel Speed

The initial speed of the wheel at full diameter should not exceed the maximum operating speed (MOS) specified on the wheel. Do not put the wheel in contact with the work piece until it is up to speed.

When is a Grinding Wheel Worn Out?

The usable portion of an abrasive wheel is that which extends beyond the mounted flanges. A wheel should not be worn down to a size which would allow the mounted flanges to come into contact with the work piece, or work piece holding fixture.



What are the Major Causes of Grinding Wheel Breakages?

A grinding wheel is a safe tool when used correctly. All Flexovit Grinding Wheels are manufactured and tested in accordance with FEPA regulations. However, when grinding wheels are shipped they may be exposed to forces that could damage them. Listed below are some of the other major causes of grinding wheel breakages:

- Using a grinding wheel damaged during transportation, storage, or as a result of careless or improper handling is extremely dangerous. Carefully inspect all grinding wheels before mounting them. NEVER MOUNT A DAMAGED GRINDING WHEEL.
- Selecting the wrong grinding wheel for the job. NEVER GRIND MATERIAL FOR WHICH THE GRINDING WHEEL IS NOT DESIGNED.
- Incorrect machine. NEVER FORCE A GRINDING WHEEL ON TO THE SPINDLE, THEY SHOULD ALWAYS BE A SLIDING FIT.
- Machine operating speed higher than grinding wheel recommended MOS. NEVER OVERSPEED A GRINDING WHEEL.
- Poor machine maintenance. FAILURE TO PROPERLY MAINTAIN A GRINDING MACHINE CAN CAUSE GRINDING WHEEL BREAKAGES RESULTING IN SERIOUS INJURY OR DEATH.
- Poor wheel balance.
- Jamming the work into the grinding wheel.
- Grinding with sufficient force so the motor slows noticeably or the work gets hot.
- Grinding on the wrong surface of a grinding wheel. i.e. On the side of a straight grinding wheel.
- For additional information on grinding wheel safety please contact your local Saint-Gobain Abrasives Customer Service Centre (contact details are given on the back cover of this catalogue).

Safety in the Use of Spindle Mounted Points

Preparation for Use

Ensure that the spindle is correctly centred in the collet or chuck, and is fixed securely. Do not allow the mounted point to rotate at a speed higher than that recommended by the manufacturer. The spindle speed in rpm must never exceed that specified. Do not put the mounted point in contact with the work piece until it is up to speed.

Personal Protection

It is recommended that safety goggles are worn.

Operation


Flexovit mounted points have 6mm spindles which should only be used with 6mm collets. To prevent the spindle becoming loose in the collet or chuck do not use excessive pressure when grinding.

Safety in the Use of Sharpening Stones

Sharpening Stones are very effective when used correctly. Following these simple guidelines will make sure that you use them safely and effectively.

Sharpening blades, knives, and other tools

There is nothing more impractical than a dull blade. With these simple steps you can restore their sharpness easily and safely.



Step 1

Place knife or blade diagonally across stone and tilt heal of blade 15 – 35 degrees to meet factory bevel angle.


Step 2

Holding wrists rigid, draw across and down from heel to tip of knife blade.

Step 3

Alternate blade sides until sharp. Do not be overly concerned about the grinding angle, but do control the consistency of the angle throughout the sharpening.

Sharpening Chisels



Step 1

First flatten the face by guiding blade across stone length using long, oval strokes until you have a uniform surface and finish.

Step 2


Establish the angle of the bevel. Holding wrists rigid, move the blade forward down the length of the stone using the whole stone width, applying pressure only in the forward motion.

Step 3

Remove wire edge by lightly stroking the stone against the cutting edge of the chisel.



Sharpening Curved General Tools



Step 1

Clamp tool handle in vice or hold by the handle.


Step 2

Apply stone at an angle parallel with bevel edge.

Step 3

Stroke in small circular motions on one side of the blade and then the other.

Knife Sharpener



Step 1

Place the sharpener on a flat surface and position the knife's edge against the stone, as shown in the diagram.

Step 2

Apply slight pressure, move the knife back and forth in a saw-like movement, so that the knife's cutting edge slides on the stone. Allow the sharpener to roll freely during this operation. Repeat the motion 10 to 15 times on each side of the cutting edge.

Step 3

To obtain a cutting edge similar to that of a blade follow the above steps and then slide each side of the blade two more times, this time applying less pressure with a very gentle motion.

COATED ABRASIVES



What is a Coated Abrasive?

Coated abrasives are generally used for sanding, deburring, scouring, polishing, and finishing applications. They are manufactured in a wide variety of forms, types, and dimensions. However, all coated abrasive products consist of the same 3 specific components, which are abrasive grain, backing material, and bond. Varying each of these components helps give each abrasive product unique qualities that make it suitable to specific applications.

Abrasive Grain

A variety of different abrasive grains are used which can be categorized into two main types:

Synthetic Abrasives

Aluminium Oxide and Silicon Carbide are the two synthetic abrasive grains used in Flexovit products. These are manufactured at very high temperatures to help produce a much harder abrasive grain. Hardness is a key requirement of an abrasive grain as it must be hard enough to cut and tough enough not to disintegrate.

- **Aluminium Oxide** is a hard abrasive grain characterized by a cool cut, long life and the ability to fracture under pressure, producing new cutting edges.
- **Silicon Carbide** is the hardest and sharpest grain used within conventional abrasives. Its extreme sharpness makes it ideal for fine finishing and its supreme hardness makes it excellent for use on stone and hard materials.

Natural Abrasives

Emery and Glass are the two natural abrasives used in Flexovit products. They are generally much softer than synthetic abrasives and are ideal for light stock removal.

Grain Distribution

There are two types of grain distribution:

Open Coat Distribution

Open Coat covers 40-60% of the backing material with grain leaving larger spaces between each grain. This makes this type of product ideal for fast removal of stock where a coarse, strong, longer lasting product is required.

Closed Coat Distribution

Closed Coat has a 100% coverage of the backing material and therefore has a high ratio of sharp grain to surface. It is recommended for use where a fine and smooth finish is required.

Backing Material

Backing Materials must be smooth enough to allow a uniform application of the adhesive coating, strong enough to withstand sanding pressures, and flexible enough to conform to the contours of the workpiece.

The Flexovit Merchandising Range includes a wide variety of backing materials including paper, cotton & polyester fabric, fibre, and non-woven materials. Also, waterproof paper products are specially treated making them suitable for use with water.



Paper

Paper is the most common backing material. The product's performance can vary as a result of the weight of the paper backing. Lighter paper is generally more flexible and heavier paper is stronger and less likely to tear.

Cloth (fabric)

Cloth backings generally give a greater level of performance than paper. They combine a high degree of flexibility, with high tensile strength making them the most durable backing material available. Cloth backed products must only be used for dry sanding and are ideal for heavy stock removal.

Fibre

Fibre backing is dense and semi-rigid. It is used exclusively for the production of fibre discs, which are ideal for working on metal.

Bond

The bond fixes the abrasive grain to the backing material. Flexovit uses two distinctly different bond applications on every product, the first to adhere the grain to the backing (make coat) and the second to anchor the grain securely in place (size coat).

There are also two different types of bond:

Natural Adhesive

Animal and vegetable adhesives for general purpose use.

Synthetic Resin

For increased durability and heavier stock removal.

Storage Conditions

Coated abrasives should be stored in dry frost free conditions. They should be kept away from cold and damp, and not be exposed to high temperature variations or direct sunlight. Excessively dry or humid storage may incur deformation.

Safety in Use

All coated abrasives should be handled carefully. Safety goggles, safety gloves, dust masks should be worn.

Safety instructions provided by machine manufacturers must be followed. Make sure the abrasive is suitable for the application before use. No modifications should be made to the product.



DIAMOND BLADES

Get the best from your Flexovit Diamond Blade

- Do not use a "wet" diamond blade for dry cutting.
- The following machine faults could affect the lifespan and performance of the diamond blade:
 - Worn or damaged bearings
 - Worn or damaged spindle
 - Loose or damaged drive belts
 - Clogged filters
 - Damaged or incorrectly sized flanges
 - Blocked water jets
 - Damaged water pump
 - Insufficient or irregular water supply
- Fit the blade so it rotates in the direction indicated.
- Check that the diamond blade is suitable for the material to be cut.
- Do not exert too much pressure let the blade do the work.
- Check that the diamond blade does not vibrate during operation.

RPM At Maximum Operating Speed 80 M/S

Diameter (mm)	Max RPM
105	15,300
115	13,300
125	12,250
150	10,200
180	8,500
200	7,650
230	6,650
250	5,100

NEVER EXCEED the maximum operating speeds:

- Hand held blades $\phi \leq 230$ mm : 80 m/s
- Hand held blades $\phi \ge 230$ mm : 100 m/s
- Others : 63 m/s



Not to be used for side grinding

Read the instructions

Wear hearing protection EN352

Wear eye protection EN166B



Wear gloves EN388 cat. 2

Wear a respirator EN149



TROUBLESHOOTING

THE DIAMOND BLADE DOES NOT CUT

Cause	The segments are too hard for the material.		
Solution	Check if the blade is suitable for the material.		
Cause	The segments have become blunt.		
Solution	Sharpen the segments by cutting an abrasive material (e.g. sandstone).		
Cause	Insufficient machine power.		
Solution	Check the voltage, machine power and filters.		
EXCESSIVE WEAR			
Cause	The segment is too soft for the material (e.g. if a blade for hard material is used to cut abrasive material).		
Solution	Check if the diamond blade is suitable for the material.		

CRACKING OF STEEL CENTRE

Cause Solution	The segments are too hard for the material. Check if the blade is suitable for the material.
Cause	Excessive cutting pressure, overheating, material slippage, twisting or jamming in the cut.
Solution	Leave the blade to do the work, do not exert too much pressure and allow the blade to cool regularly by leaving it to rotate away from the work piece for a few seconds.

LOOSENING OR CRACKING OF SEGMENTS

Cause	The segments are too hard for the material. This results in the diamond blade
	bouncing in the cut resulting in cracking segments.
Solution	Check if the diamond blade is suitable for the material.

SCORCHING OF SEGMENTS

Cause Solution	Excessive cutting pressure causing overheating. This is easily recognisable from the blue colouring where the segments and the steel core are welded together. Allow the diamond blade to cool regularly by rotating the blade away from the work piece for a few seconds.	
Cause Solution	The segments are too hard for the material. Check if the diamond blade is suitable for the material. Alternatively use less cutting pressure and let the blade do the work.	
UNDERCUTTING		

Cause	Undercutting occurs when the steel core wears faster than the segment, i.e. where the segment and steel core meet. This is usually caused by materials that are highly abrasive. The cutting debris is not removed sufficiently and the steel core is affected. Undercutting is certain to occur if a diamond blade for hard materials is used to cut abrasive materials.
Solution	Use a diamond blade suitable for the specific material.

SAFETY ADVICE – DO'S:

For your safety you should ensure that you are fully aware of how to safely use diamond blades.

DO Read the safety instructions provided by the abrasives and equipment supplier

DO Store abrasives in dry, frost-free conditions avoiding wide variations in temperature

DO Ensure that the product is suitable for its purpose

DO Handle, store and transport products with care

DO Disconnect the power to the machine before fitting the product

/

DO Examine all products before mounting and periodically during blade us for possible defects or damage (core flatness, fatigue cracks, undercutting, arbor hole damage...)

- **DO** Check that correct mounting devices are used and that they are clean, undistorted and free from burrs
- **DO** Ensure that work rests are properly adjusted and secure

DO Always use a correctly designed and adjusted guard (on the blade and belts)

DO Ensure that the workpiece is secure

DO Wear appropriate personal protective equipment at all times

DO Avoid clogging and uneven wear to ensure that the product is working efficiently

DO Ensure accordance between product direction arrow / machine rotation

DO Ensure that all machines using abrasives meet the requirements of the current european machinery directives-CE

DO Be aware of the hazards likely during the use of abrasives and observe the recommended precautions to be taken:

- Bodily contact with the abrasive product at operating speed
- Injury resulting from product breakage during use
- Grinding debris, sparks, fumes and dust generated by the grinding process
- Noise
- Vibration



SAFETY ADVICE – DON'TS:

For your safety you should ensure that you are fully aware of how to safely use diamond blades.

X	DON'T Allow untrained people to use abrasives
X	DON'T Use a product that is damaged or one which has been dropped
X	DON'T Use a product if it cannot be properly identified
X	DON'T Use a machine that is not in good working order or one with defective parts
X	DON'T Force the abrasive onto the mounting device or modify the size of the mounting hole
X	DON'T Exceed the maximum operating speed marked on the product
X	DON'T Apply shock or excessive force to the product or let it overheat
X	DON'T Use mounting flanges which are not clean and flat
X	DON'T Tighten the mounting device excessively
X	DON'T Start the machine until the guard is in place and fastened securely
X	DON'T Continue to use a product if vibration occurs. True or replace it
X	DON'T Grind on the part of the product which is not designed for the operation
X	DON'T Start the machine with the workpiece in contact with the abrasive product
X	DON'T Grind material for which the product is not designed
X	DON'T Stop the abrasive by applying pressure to its surface, let it stop naturally
X	DON'T Exceed permissible rotation speeds: refer to values engraved on product
X	DON'T Use blades with missing segments or core cracks
X	DON'T Use dry products marked for wet use
X	DON'T Wear loose clothing, ties and jewellery
X	DON'T Use abrasive products near flammable materials




meels Section	13 19	6	
rpe 42 (s Type 41	16		aging Cu ograms
D	44		shing Compo ishing Products
ding Sheets anding Sheets	45 53	Po	lishing Sponge
and Blades Sector	56	P	OP Programme ower File Sanding Be PRO Icons
ilding Materiais Con	58		
amic and Storie	5	57	Quick Release Orbita
nond Blades – norete and Reinforced Concrete		59	Safety, Health, an
and Blades		43	Saint-Gobain
intable Discs		40 32	Sanding P Sandi

NOTES AND INDEX

- 84 Notes
- 86 Index







NOTES







INDEX

R R	
Accessories Section	61
В	
Bonded Abrasives Section	21
Buffing And Polishing Products	
Buffing Wheels	
С	
Coated Abrasives Section	27
Crimped Steel Wire Cup Brushes	65
Crimped Steel Wire Wheels	
Cutting-Off and Grinding Wheels Section	13
Cutting-Off Wheels Type 42	
Cutting-Off Wheels Type 41	
D	

Delta Sanding Sheets	
Detail Sanding Sheets	.45
Diamond Blades Section	
Diamond Blades –	
Building Materials General Purpose	56
Diamond Blades –	
Ceramic and Stone Tiles	.58
Diamond Blades –	
Concrete and Reinforced Concrete	57
Diamond Blades –	
Roof Tiles, Granite and Hard Materials	
Drill Mountable Discs	

Е

Eccentric Discs	
Emery Cloth Sheets	
F	
FEPA	
Fibre Discs	
Fibreflex Discs	
Finishing Paper Rolls	
Finishing Paper Sheets	
Flap Discs	
Fleece Bonnet	
Flexovit Brand History	
G	
General Purpose Rolls	
General Purpose Sheets	
Glass Paper Sheets	
Grinding Wheels Type 27	20

Hand Sanding Sheets	.30
High Performance Rolls	.35
High Performance Sheets	
How To Order	
How To Use This Catalogue	6

Н

K	
Knife Sharpener	.25
Μ	
Merchandising Options	12
Mounted Points	.25
Multi Sanding Sheets	44
N	
Non Woven Abrasive Pads	.33
0	
Orbital Sheets	37
OSA	7
Р	
Packaging Communication	9
Pictograms	
Polishing Compound Blocks	
Polishing Products	
Polishing Sponge POP Programme	
Power File Sanding Belts	
PRO Icons	
0	
Quick Release Orbital Sheets	37
S	
Safety, Health, and Environment Saint-Gobain – A Corporate Perspective Sanding Belts Sanding Block Kits and Refills Sanding Discs Sanding Rolls Sanding Sponges Sharpening Stones Steel Wire Brushes Steel Wire Cup Brushes Steel Wire End Brush Steel Wire Wheels and Brushes	50 40 35 50 24 64 65 64
т	
Technical Information	69
Technical Information – Bonded Abrasives Technical Information – Coated Abrasives Technical Information –	77
Cutting-Off and Grinding Wheels	
Technical Information – Diamond Blades Twisted Knot Steel Wire Cup Brush	
U	
Understanding The Flexovit Product Range	10
V	
Vitrified Bench Wheels	26
W	
Waterproof Paper Sheets	33

SAINT-GOBAIN ABRASIVES GmbH TEISENBERGGASSE 37 A- 5020 SALZBURG AUSTRIA TEL: +43 662 430 076 FAX: +43 662 430 175

SAINT-GOBAIN ABRASIVES N.V. HEIDE 10 1780 WEMMEL BELGIUM TEL: +32 2 267 21 00 FAX: +32 2 267 84 24

SAINT-GOBAIN ABRASIVES, S.R.O. VINOHRADSKÁ 184 130 52 PRAHA 3 CZECH REPUBLIC TEL: +420 267 132 026 +420 267 132 029 FAX: +420 267 132 021-2

SAINT-GOBAIN ABRASIVES A/S KORSKILDEENG 5 DK-2670 GREVE DENMARK TEL: +45 467 552 44 FAX: +45 467 550 60

SAINT-GOBAIN ABRASIFS PO BOX 18260 SUITE 404/405 - LOB17 JEBEL ALI FREE ZONE DUBAI - UNITED ARAB EMIRATES TEL: +971 4 88 17 836 FAX: +971 4 88 73 210

SAINT-GOBAIN ABRASIFS RUE DE L'AMBASSADEUR - B.P.8 78 702 CONFLANS CEDEX FRANCE TEL: +33 (0)1 34 90 40 00 FAX: +33 (0)1 39 19 89 56

SAINT-GOBAIN ABRASIVES GmbH BIRKENSTR. 45-49 D-50387 WESSELING GERMANY TEL: +49 2236 703-1 +49 2236 8996-0 FAX: +49 2236 703-367 +49 2236 8996-10

SAINT-GOBAIN ABRASIVES KFT. H-1225 BUDAPEST BÁNYALÉG UTCA 60/B. HUNGARY TEL: +36 1 371 22 50 FAX: +36 1 371 22 55 SAINT-GOBAIN ABRASIVI S.p.A VIA PER CESANO BOSCONE 4 I-20094 CORSICO MILANO ITALY TEL: +39 024 4851 FAX: +39 02 - 44 78 266

SAINT-GOBAIN ABRASIVES S.A. 190 RUE J.F. KENNEDY L-4930 BASCHARAGE GRAND DUCHE DE LUXEMBOURG TEL: +352 50 401 1 FAX: +352 50 16 33 NO. VERT (France) 0800 906 903

SAINT-GOBAIN ABRASIFS, S.A. 2 ALLÉE DES FIGUIERS AÏN SEBAÂ - CASABLANCA MOROCCO TEL: +212 22 66 57 31 FAX: +212 22 35 09 65

SAINT-GOBAIN ABRASIVES BV GROENLOSEWEG 28 7151 HW EIBERGEN P.O. BOX 10 7150 AA EIBERGEN THE NETHERLANDS TEL: +31 545 466466 FAX: +31 545 474605

SAINT-GOBAIN ABRASIVES AS VESTVOLLVEIEN 6D 2019 SKEDSMOKORSET NORWAY TEL: +47 63 87 06 00 FAX: +47 63 87 06 01

SAINT-GOBAIN ABRASIVES Sp.z o.o UL. TORUNSKA 239/241 62-600 KOLO POLAND TEL: +48 63 26 17 100 FAX: +48 63 27 20 401

SAINT-GOBAIN ABRASIVOS, L. da ZONA INDUSTRIAL DA MAIA I-SECTOR VIII, No. 122 APARTADO 6050 4476 - 908 MAIA PORTUGAL TEL: +351 229 437 940 FAX: +351 229 437 949 SAINT-GOBAIN ABRASIVI SRL PARC INDUSTRIAL HOLROM DRUM CAREI NR. 11 447355 VETIS JUD. SATU-MARE ROMANIA TEL: +40 261 450 009 FAX: +40 261 750 010

SG HPM RUS 58, F. Engels Str. Stroenie 2 105082 Moscow Russia TEL: +74 955 408 355 FAX: +74 959 373 224

SAINT-GOBAIN ABRASIVES (PTY) LTD 2 MONTEER ROAD ISANDO 1600 P.O. BOX 67 SOUTH AFRICA TEL: +27 11 961 2000 FAX: +27 11 961 2184/5

SAINT-GOBAIN ABRASIVOS, S.A. CTRA. DE GUIPÚZCOA, KM. 7,5 E-31195 BERRIOPLANO (NAVARRA) SPAIN TEL: +34 948 306 000 FAX: +34 948 306 042

SAINT-GOBAIN ABRASIVES AB BOX 305 SE-177 25 JÄRFÄLLA SWEDEN TEL: +46 8 580 881 00 FAX: +46 8 580 881 01

SAINT-GOBAIN ABRASIVES BUYUKDERE CAD. BAHCELER SOK. EFE HAN No.20, K1 MECIDIYEKOY 34 394 ISTANBUL TURKEY TEL: +90 -212-288 63 71 FAX: +90 212 275 6734

SAINT-GOBAIN ABRASIVES LTD. DOXEY RD STAFFORD ST16 1EA UNITED KINGDOM TEL: +44 1785 222 000 FAX: +44 1785 213 487

SAINT-GOBAIN A B R A S I V E S

Saint Gobain Abrasifs European Headquarters Rue de l'Ambassadeur - B.P.8 78 702 Conflans Cedex France

Tel: +33 (0)1 34 90 40 00 Fax: +33 (0)1 39 19 89 56

Form # 1291